





































































MADE IN ITALY



ADBLUE® PRODUCT RANGE

PRODUCT RANGE	PRODUCT CATEGORY		PRODUCT		PAGE	
CAR FILLING 	FILLING SYSTEMS			DELPHIN PRO_X	8	
				DELPHIN PRO	10	
				DELPHIN PRO IBC	12	
				PIUSIBOX CAR SUCTION	14	
FUEL MANAGEMENT SYSTEMS 	FUEL MANAGEMENT SYSTEMS			OVERVIEW	20	
		SOFTWARE		B.SMART	22	
					ADD-ONS	24
		DISPENSER		SELF SERVICE B.SMART	26	
		CONTROL BOX		MCBOX B.SMART	28	
		SOFTWARE		SSM2.0	30	
				DATA TRANSFER SSM 2.0	32	
				SSM 2.0 CLOUD	34	
		DISPENSER		SELF SERVICE MC 2.0	36	
		CONTROL BOX		MCBOX 2.0	38	
			SOFTWARE		SSM 2018	40
				DATA TRANSFER SSM 2018	42	
		DISPENSER		SELF SERVICE MC	44	
		CONTROL BOX		MCBOX	46	
KITS 	DRUM			SUZZARABLU DRUM	52	
	IBC			THREE25	54	
				SUZZARABLU PRO/BASIC	56	
	MOBILE			SUZZARABLU PORTABLE KIT	58	
				PIUSIBOX FOR ADBLUE®	60	
	ST			SUZZARABLU BOX	62	
PUMPS 	AC PUMP			SUZZARABLU PUMP AC	68	
	DC PUMP			SUZZARABLU PUMP DC	70	
	SUBMERSIBLE PUMP			SQUALO35	72	
	PNEUMATIC DIAPHRAGM PUMPS			MP 130	74	
				MP 140	76	
				MP 180	78	
				MP 190	80	
					PIUSI HAND PUMP	82
	HAND PUMPS			PIUSI HAND PUMP IBC	84	
				SUZZARABLU HAND PUMP	86	
METERS 	ELECTRONIC METERS			K24	92	
				TURBINOX	94	
				MK325 METER	96	
				REMOTE DISPLAY	98	
METERED NOZZLES 	AUTOMATIC METERED NOZZLES			SB325_X METER	104	
				K24 A60 AUTOMATIC NOZZLE	106	
	MANUAL METERED NOZZLE			K24 SUZZARABLU MANUAL NOZZLE	108	
NOZZLES 	AUTOMATIC NOZZLES			SB325_X	110	
				SUZZARABLU A60	112	
	MANUAL NOZZLE			SUZZARABLU MANUAL NOZZLE	118	

All Pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.


PRODUCT RANGE	PRODUCT CATEGORY	PRODUCT	PAGE
FILTRATION 	FILTER	 3D FILTER	124
TANK MONITORING 	TANK LEVEL INDICATOR	 OCIO	128
HOSE REEL 	OPEN HOSE REEL	 ADBLUE® HOSE REEL	130
ACCESSORIES 	ACCESSORIES	 CONNECTIONS&CONNECTORS	140
		 COUPLING&FITTINGS	142
		 HOSE&SWIVEL	144
MERCHANDISE 	MERCHANDISE		148


JOURNEY

THE HISTORY OF KNOW-HOW

ABOUT US

PIUSI was established in 1953 in Suzzara, in the province of Mantua (Italy). For more than 60 years, PIUSI has been the major player in the world's leading markets with its full range of products for transferring, refilling and measuring lubricants, fuels and liquids such as gasoline, diesel, Diesel Exhaust Fluid (DEF), oil, water and grease. Some of PIUSI's main products include pumps, flow meters, nozzles, dispensers, hose reels, liquid level gauges, software and complete kits used by operators in agriculture, the automotive industry, workshops and garages, fleet management and transport by road and by sea. PIUSI products have many different uses such as monitoring and transferring fuel at trucking companies, refueling of agricultural vehicles, transferring fuels in construction and mining for heavy duty vehicles. The products are intuitive and easy to use; are suitable to be installed in a variety of contexts; are all made entirely in Italy; and all products express the innovation, quality, professionalism and R&D that have always distinguished PIUSI. Its headquarters are in Suzzara (Mantova - 150 km from Milan and Venice). The company currently employs more than 250 employees between sales, administration, R&D, production and logistics. PIUSI products are sold in more than 120 countries around the world thanks to a large network of distributors and the US branch based in Fort Lauderdale, FL, serving the North and South American markets.







CAR FILLING

A large, solid red triangle is positioned in the bottom right corner of the page, pointing towards the top right.



CAR FILLING



FUEL MANAGEMENT
SYSTEMS



KITS



PUMPS



METERS



METERED NOZZLES

DELPHIN PRO_X

FEATURES

- FULLY AUTOMATIC
- 100% COMPATIBLE WITH ALL CARS AND VEHICLES**
- AUTOMATIC FLOW RATE REGULATION
- PRESET QUANTITY

DELPHIN PRO_X is the latest innovation within the PIUSI AdBlue® car filling equipment: preset function, automatic FLOW RATE regulation and visual diagnostic alert are just few of its main new features. This dispenser comes both in AC and DC version, and, thanks to the sturdy and adjustable cart, it can easily support 60/200 ltrs drums.

The AUTOMATIC FLOW RATE function adjust the FLOW RATE according to the vehicle's tank. While the PRESET allow to pre-define the total amount of AdBlue® to be filled in the car tank.

PERFORMANCE

2-15 L/MIN

FLOW RATE

AC/DC

VOLTAGE
POWER

2M

HOSE LENGTH



DELPHIN PRO_X



PACKAGING

CODE	WEIGHT		PACKAGING			
	KG	LBS	MM	INCH	PCS/PALLET	PCS/BOX
FO0100400	43,5	96	770X1080X800	0,3X42,1X31,5	4	1
FO0100410	51	112,5	770X1080X800	0,3X42,1X31,5	4	1



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL



WATER



WINDSCREEN

FUNCTIONING



AUTOMATIC FLOW RATE

The fastest automatic way to refill any car. Thanks to this option, DELPHIN PRO_X automatically adjust the flow rate according to the vehicle's tank.



PRESET

By pre-setting the needed quantity the operator can concentrate on something else while DELPHIN PRO_X is refilling. DELPHIN PRO_X will stop automatically when the preset quantity will be reached.

IN THE BOX

- DELPHIN PRO_X UNIT
- AF2 CONNECTOR
- INSTRUCTION MANUAL

DETAILS




UNIVERSAL ISO CONNECTOR



AF2 CONNECTOR

DIMENSIONS



Dimensions expressed in millimeters

MATERIALS

- PUMP:
- BODY: POLIPROPYLENE
- DIAPHRAGM: POLIPROPYLENE

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		VOLTAGE			HOSE		ON/OFF
			L/MIN	GPM	AC V/HZ DC VOLT	POWER WATT	AMP. MAX.	LENGHT	Ø	SWITCH
FO0100400	DELPHIN PRO_X AC		2 - 15	0,5 - 4	230/50	260	2,2	2 M	3/4"	YES
FO0100410	DELPHIN PRO_X DC		2 - 15	0,5 - 4	230/50**	260*	2,2**	2 M	3/4"	YES

* BATTERY CHARGER

**IN ACCORDANCE TO ISO/FDIS 22241-4:2009

DELPHIN PRO_X

FILLING SYSTEMS

9



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

DELPHIN PRO

FEATURES

- FULLY AUTOMATIC
- NO OPERATOR NEEDED
- 100% COMPATIBLE WITH ALL CARS AND VEHICLES**
- STURDY DESIGN
- EASY TO HANDLE
- FLOW RATE REGULATOR

DELPHIN PRO is the most famous PIUSI AdBlue® car filling system: it allows any garage to enter into the automatic car filling of AdBlue® stopping the use of manual tanks. Compact, mobile, reliable and robust, DELPHIN PRO can be used in every working condition. It is fully automatic - it will only take 2 minutes for a full AdBlue® tank - and its patented spout prevents AdBlue® from crystallizing and never requires cleaning or servicing.

PERFORMANCE

2-11 L/MIN

FLOW RATE

AC
VOLTAGE

POWER

2M

HOSE LENGTH

**DELPHIN PRO**

PACKAGING

CODE	WEIGHT		PACKAGING		
	KG	LBS	MM	INCH	PCS/BOX
FO010020B	37	81,5	770X1080X800	0,3X42X31,5	1
FO010021B	37	81,5	770X1080X800	0,3X42X31,5	1



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL



WATER



WINDSCREEN

FUNCTIONING



1
ACTIVATE
DELPHIN PRO



2
USE THE DIMMER
TO ADJUST
THE FLOW RATE



3
CONNECT THE
CONNECTOR
TO THE TANK
OF THE CAR



4
PRESS THE
REFILL BUTTON
FOR 5 SECS



5
ONCE THE TANK IS
FULL, DELPHIN PRO
AUTOMATICALLY
STOPS DISPENSING

IN THE BOX

- DELPHIN PRO UNIT
- AF2/SEC CONNECTOR
- INSTRUCTION MANUAL

DETAILS



UNIVERSAL ISO CONNECTOR




SEC VERSION AVAILABLE



DIGITAL FLOW METER

DIMENSIONS



Dimensions expressed in millimeters

MATERIALS

- PUMP:
- BODY: POLIPROPYLENE
- DIAPHRAGM: POLIPROPYLENE

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		VOLTAGE			HOSE		ON/OFF
			L/MIN	GPM	AC V./HZ DC VOLT	POWER WATT	AMP. MAX.	LENGHT	Ø	SWITCH
FO010020B	DELPHIN PRO 120/230V-50/60HZ		2 - 11	0,5 - 2,9	230/50	400	1,95	2 M	3/4"	YES
FO010021B	DELPHIN PRO 120/230V-50/60HZ W/SEC CONN		2 - 11	0,5 - 2,9	230/50	400	1,95	2 M	3/4"	YES

**IN ACCORDANCE TO ISO/FDIS 22241-4:2009

DELPHIN PRO

FILLING SYSTEMS

11



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

DELPHIN PRO IBC

FEATURES

- FULLY AUTOMATIC
- 100% COMPATIBLE WITH ALL CARS AND VEHICLES**
- STURDY DESIGN
- EASY TO INSTALL
- FLOW RATE REGULATOR
- SPECIFICALLY DESIGN FOR IBC TANKS

DELPHIN PRO IBC is a compact and professional solution for an AdBlue® car filling fixed installation. It benefits from all the features of Delphin Pro AC while being suitable for all situations with a higher consumption of AdBlue®. It is designed to be hung on IBC tanks guaranteeing maximum security and reliability thanks to the lock bracket system. The integrated handle allows a safe and easy lifting. The flat bottom allows to place DELPHIN PRO IBC firmly on the floor during the IBC tank replacement or any other operation.

PERFORMANCE

2-11 L/MIN

FLOW RATE

AC
VOLTAGE
POWER

6M

HOSE LENGTH

AVAILABLE WITH
ON/OFF
BUTTON
SWITCH

**DELPHIN PRO IBC**

IMBALLAGGIO

CODE	WEIGHT		PACKAGING		
	KG	LBS	MM	INCH	PCS/BOX
FO0100B0A	24	52,9	500X340X590	19,7X13,4X23,2	1
FO0100B2A	24	52,9	500X340X590	19,7X13,4X23,2	1



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL



WATER



WINDSCREEN

FUNCTIONING



1
ACTIVATE
DELPHIN PRO



2
USE THE DIMMER
TO ADJUST
THE FLOW RATE



3
CONNECT THE
CONNECTOR
TO THE TANK
OF THE CAR



4
PRESS THE
REFILL BUTTON
FOR 5 SECS



5
ONCE THE TANK IS
FULL, DELPHIN PRO
AUTOMATICALLY
STOPS DISPENSING

IN THE BOX

- DELPHIN PRO IBC UNIT
- AF2 / SEC CONNECTOR
- INSTRUCTION MANUAL

DETAILS



UNIVERSAL ISO CONNECTOR



AF2 CONNECTOR INCLUDED




SEC VERSION INCLUDED



DIGITAL FLOW METER

DIMENSIONS



Dimensions expressed in millimeters

MATERIALS

- PUMP:
- BODY: POLIPROPYLENE
- DIAPHRAGM: POLIPROPYLENE

DATI TECNICI

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		VOLTAGE			HOSE		ON/OFF
			L/MIN	GPM	AC V/HZ	POWER WATT	AMP. MAX.	LENGHT (M)	Ø (MM)	SWITCH
FO0100BOA	DELPHIN PRO IBC AF2-SEC 230V/50HZ		2 - 11	0,5 - 2,9	230/50	400	1,95	3	19	SI
FO0100B2A	DELPHIN PRO IBC AF2-SEC 230V/50HZ 6 MT		2 - 11	0,5 - 2,9	230/50	400	1,95	6	19	SI

**IN ACCORDANCE TO ISO/FDIS 22241-4:2009

DELPHIN PRO IBC

FILLING SYSTEMS

13



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

PIUSIBOX CAR SUCTION

FEATURES

- IDEAL TO EMPTY VEHICLE TANKS
- IT AVOIDS THE TANK OVERFILLING
- SUZZARABLUE DIAPHRAGM PUMP
- EASY TO HANDLE

The PIUSI BOX CAR SUCTION is the perfect solution for those who need to drain an AdBlue® vehicle tank before servicing. It comes with a portable box that contains all the required equipment.

PERFORMANCE

UP TO

34 L/MIN

FLOW RATE

AC

VOLTAGE

POWER

MAX

2M

BOUND

HOSE LENGTH



PIUSIBOX CAR SUCTION



PACKAGING

CODE	WEIGHT		PACKAGING		
	KG	LBS	MM	INCH	PCS/BOX
FOO201R20	11,5	25,3	650X400X450	25,6X15,7X17,7	1



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER




WINDSCREEN

FUNCTIONING



DIMENSIONS



Dimensions expressed in millimeters

IN THE BOX

- SUZZARABLU PUMP
- SUCTION/DELIVERY HOSE
- INSTRUCTION MANUAL

DETAILS



ON/OFF SWITCH



SUZZARABLU PUMP AC



HANDLE

MATERIALS

- PUMP:
BODY: POLIPROPYLENE
DIAPHRAGM: POLIPROPYLENE

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		VOLTAGE			RPM	DUTY CYCLE		CABLE	SUCTION HOSE 12 MM Ø	DELIVERY HOSE 12 MM Ø
			L/MIN	GPM	AC V/Hz DC VOLT	POWER WATT	AMP. MAX.		RPM	MIN		LENGHT (M)	LENGHT (M)
FOO201R20	PIUSIBOX CAR SUCTION ADBLUE		34	9	230/50	400	1,95	1450	20	YES	YES	2	2

PIUSIBOX CAR SUCTION






FILLING SYSTEMS






15








CAR FILLING ACCESSORIES

FILLING SYSTEMS

DELPHIN PRO_X	CODE	DESCRIPTION	
	F21614000	TANK RECOVERY SYSTEM DELPHIN PRO	   
	F2142100A	ADAPTER 3/4" 70X6 DELPHIN	
	F15452000	SEC + HOSETAIL 90°	
	F20189000	AF2 56X4 BUTTRESS - 1"BSP	
	F20190000	AF2 2" BUTTRESS - 1" BSP	
	F20257000	AF2 2" BSP - 1" BSP	
	F20258000	AF2 2" 70X6 - 1" BSP	

DELPHIN PRO	CODE	DESCRIPTION	
	F20189000	AF2 56X4 BUTTRESS - 1"BSP	   
	F20190000	AF2 2" BUTTRESS - 1" BSP	
	F20257000	AF2 2" BSP - 1" BSP	
	F20258000	AF2 2" 70X6 - 1" BSP	
	F21614000	TANK RECOVERY SYSTEM DELPHIN PRO	
	F2142100A	ADAPTER 3/4" 70X6 DELPHIN	
	F15452000	SEC + HOSETAIL 90°	

DELPHIN PRO IBC	CODE	DESCRIPTION	
	F20189000	AF2 56X4 BUTTRESS - 1"BSP	   
	F20190000	AF2 2" BUTTRESS - 1" BSP	
	F20257000	AF2 2" BSP - 1" BSP	
	F20258000	AF2 2" 70X6 - 1" BSP	
	F12511000	VAPOUR RECOVERY DELPHIN PRO IBC	
	F2193800A	AF2 56X4 BUTT. - 1"BSP SUCTION CONNECTOR	
	F2193900A	AF2 2" BSP - 1" BSP SUCTION CONNECTOR	





FUEL MANAGEMENT SYSTEMS



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

OVERVIEW

FEATURES:

ACCURATE DATA

- REAL AND ACCURATE CONSUMPTIONS' DATA ON EACH REFUELLING OPERATION MANAGED AUTOMATICALLY BY THE SYSTEM;

- OVERVIEW ON CONSUMPTIONS' TREND AND AVAILABLE RESIDUAL AdBlue®/DEF;

REDUCED COSTS

- CAREFUL AND MEASURED CONSUMPTION OF AdBlue®/DEF ALLOWS TO SAVE UP TO 20% OF FLUID EVERY YEAR

NO ABUSE

- A FUEL MANAGEMENT SYSTEM ALLOWS YOU TO TRACK WHO IS MAKING THE PROCEDURE, ON WHICH VEHICLE ALSO INDICATING THE DISPENSER USED IN ORDER TO CONTAIN ABUSES.

Fuel Management Systems (FMS) are technologically-advanced equipment that allow to measure, control and manage the consumptions of AdBlue®/DEF (or other fluids) of fleets or other Company vehicles (such as for example the earth moving machines within the construction industry).

The consumption of AdBlue®/DEF and fuel is an important part of the running costs of a fleet.

How much AdBlue®/DEF have you wasted in the past few months?

How much AdBlue®/DEF does each vehicle or driver consume?

What was the trend of consumptions?

To have a clear and precise overview on the situation, you need a FMS.

A system linked to your dispensers and stations for AdBlue®/DEF transferring that follow and trace all the refuelling operations also indicating who is the operator and the vehicle which is refuelled; all in real time.

PIUSI has developed 3 different FMS software for AdBlue®/DEF suitable for all different requirements: B.SMART, SSM 2.0 and SELF SERVICE MANAGEMENT 2018.

SELF SERVICE[®]
MANAGEMENT
2018



B.SMART



SSM 2.0[®]
SELF SERVICE MANAGEMENT





NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL



WATER



WINDSCREEN

Why choose a PIUSI FMS?

With **70 years of history**, PIUSI can supply not only all the technological and IT aspects of the software, but also - integrated - a wide range of dispensers suitable for all needs.

By choosing PIUSI, you will have - from a single supplier - not only the Software, but also the dispensing Hardware directly from the same Company.

		SELF SERVICE [®] MANAGEMENT 2018	SSM 2.0 [®] SELF SERVICE MANAGEMENT	B.SMART
GENERAL	PLATFORM	PC Software	PC Software	Cloud Software
	MULTISITE	NA	with SSM2.0 Cloud	YES
	MAX USERS	120/Dispenser	up to 1000	Unlimited
	MAX DISPENSERS	16	up to 20	Unlimited
	USER LOGIN	iButton/Pincode	iButton/Pincode	Mobile App*
LIMIT SETTINGS	REMOTE USER/DISPENSER DEACTIVATION	NA	YES	YES
	USER DAY/WEEKLY LIMITS	NA	YES	COMING UP
	VEHICLE LIMITS	NA	YES	COMING UP
MANAGEMENT: • VEHICLES • SUPPLIERS • CONSUMPTIONS	REGISTRATION NUMBER	Manual entry	iButton	Mobile App
	USER VEHICLE ASSIGNMENT	NA	YES	COMING UP
	ODOMETER	YES	YES	YES
	EXTERNAL TRANSACTIONS	NA	YES	COMING UP
	FUEL CONSUMPTION MANAGEMENT	NA	YES	COMING UP
	ADBLUE CONSUMPTION MANAGEMENT	NA	YES	COMING UP
	FLUID SUPPLIERS MANAGEMENT	NA	YES	COMING UP
TANK LEVEL MANAGEMENT	TANK LOW LEVEL PUMP CUT-OFF	YES	YES	YES
	REMOTE TANK LEVEL MANAGEMENT	NA	YES	with Tank Watchdog Add-on
	MAX NO. OCIO	NA	up to 20	Unlimited - with Tank Watchdog Add-on
TANK ALARM	SOFTWARE ALARMS	NA	YES	YES
	HARDWARE ALARMS (W/OCIO)	YES	YES	YES
REPORT	TRANSACTION REPORT	YES	YES	YES
	TANK LEVEL REPORT	NA	YES	with Tank Watchdog Add-on
	FUEL PRICE TREND REPORT	NA	YES	with Tank Watchdog Add-on
	TRANSACTION GEOLOCALIZATION	NA	NA	with Mobile Add-on

*IBUTTON: IN CASE OF EMERGENCY IF/OR SMARTPHONE IS ABSENT OR IT DOESN'T WORK

OVERVIEW



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

B.SMART

FEATURES

- **SIMPLE, INTUITIVE, SUITABLE FOR EVERYONE**
- **UNLIMITED TO FIT ALL NEED**
- **MONO OR MULTI-SITE**
- **SOFTWARE ALWAYS INCLUDED WITH THE DISPENSER**
- **BLUETOOTH**
- **CLOUD-BASED**
- **NO SOFTWARE INSTALLATION**
- **NO FEE**
- **ANALYSIS, CONTROL AND MANAGEMENT IN ONE CLICK**

PERFORMANCE

DATA AVAILABLE ALWAYS TRANSACTIONS	NO SOFTWARE ON THE PC CLOUD
NO FEE UTILIZATION	ONLY BLUETOOTH NO WI-FI OR LAN CONNECTION

B.SMART is the Fuel Management System (FMS) by PIUSI designed and engineered for fleets of all sizes: small, medium, large, mono or multi-site. Innovative, simple and smart - the name carries its meaning - PIUSI B.SMART combines the quality and efficiency of PIUSI dispensers, with a Cloud-based software (APP for drivers and a web APP for fleet managers) driven by Bluetooth technology; that means no Wi-Fi or LAN network are required. Thus, it is possible to use B.SMART wherever; also in the more distant areas.

A FMS all in one: the fleet manager has just to choose the necessary dispensers; the software is always included in the "package" (no rental ore recurring fee will be required).




B.SMART

B.SMART is flexible and expandable: the same system easily fits to all requirements. It is only necessary to add the add-on needed to keep up with the evolution of the fleet.

B.SMART API AVAILABLE

THE B.SMART API ALLOWS
YOU TO CONNECT AND
EXCHANGE DATA WITH
PLATFORM.





NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE




OIL



WATER



WINDSCREEN



APP

Dedicated to drivers, the APP for drivers just needs a smart device with Bluetooth to work properly: once the APP is open, the smartphone or tablet immediately connects to the dispenser to start the refueling operation.



HARDWARE

PIUSI B.SMART runs only with the dedicated range of dispensing devices: quality guaranteed by PIUSI; the highest technical performances and reliability, all form a unique supplier. Real time communication between the dispenser and the PC.



CLOUD

The core of B.SMART fuel management software is a Cloud-based service that tracks every refuelling operation and keeps every device synchronized.



WEB APP

Dedicated to fleet manager. No software installation: just log in and start immediately to monitor, manage and control consumptions of the fleet.

B.SMART



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES


ADD-ONS

FEATURES

- **EXPANDABLE WITH DEDICATED ADD-ON**
- **UNLIMITED DRIVERS**
- **DETAILED INFO FOR EACH DRIVER**
- **SUITABLE FOR ALL NEED**
- **MONITORING AND MANAGEMENT OF THE TANKS**

PIUSI B.SMART is an expandable system that quickly adapts to the new needs thanks to software-activated addons. A smart FMS that grows with the business. With the ADD-ON packages it is possible to purchase drivers accesses (5, 10 or 50) or the special function TANK WATCHDOG* to have always under control the level of the fluid in the tank.

You can also upgrade your MC version to B.SMART with the dedicated kit hardware 1.0/2018 upgrade.



TANK WATCHDOG

B.SMART Tank Watchdog is the perfect add on for a complete and updated control of the stock.

It allows you to:

- monitor the tank level (add fluid loads and unloads and adjustments);
- set level alarms;
- manage suppliers;
- follow inventory price values and trends;
- access and download reports from anywhere.

ADD-ON

Once the ADD-ON is chosen, PIUSI will send an activation code with all related instructions.

DRIVER ADD-ON

CODE	DESCRIPTION
FO0770D00	DRIVER ACCESS ADD-ON B.SMART (X5)
FO0770D10	DRIVER ACCESS ADD-ON B.SMART (X15)
FO0770D20	DRIVER ACCESS ADD-ON B.SMART (X50)

TANK WATCHDOG ADD-ON (available from september 2020)

CODE	DESCRIPTION
FO0770L00	B.SMART TANK WATCHDOG ADD-ON - 1 YEAR
FO0770L10	B.SMART TANK WATCHDOG ADD-ON - 3 YEARS
FO0770L20	B.SMART TANK WATCHDOG ADD-ON - ONE TIME FEE

* ONLY WITH THE PURCHASING OR THE PRESENCE IN THE SYSTEM OF OCIO 2.0



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL



WATER




WINDSCREEN



TANK WATCHDOG - tank levels

Adding the level indicator OCIO, the system allows you to monitor the fluid level in your tanks in real time and gives alarms in case of malfunction or low levels. A perfect add on for a complete and updated control of the stock. You can connect also any 420 mA or 0-10 V fluid gauge or run the system without any gauge thanks to the “virtual tank” option:

- set level alarms and get notifications on the tank level;
- possibility to configure high level or low level alarms;
- stop the pump according to the level of the fluid;
- send an automatic e-mail to notify when you reach the level alarm set.



TANK WATCHDOG - fluid price and values

Thank to the level indicator OCIO you can have at your fingertips the fluid inventory value & quantity: you can define the refuelling price and verify the current inventory value.

- manage suppliers of the fluids to keep track of the date, price and quantity bought;
- get real time data of the value of your inventory;
- follow fluids price trends;
- access and download reports from any internet connected device thanks to the software cloud.

ADD-ONS



B.SMART SOFTWARE

25



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

SELF SERVICE B.SMART

FEATURES

- ACCESS CONTROL AND MANAGE ADBLUE® DELIVERY
- 3D FILTER INTEGRATED
- COMPACT DESIGN
- NATIVE WITH B.SMART CLOUD SOFTWARE
- KIT UPGRADE 1.0/2018 AVAILABLE

SELF SERVICE B.SMART for AdBlue® is the updated version of the famous PIUSI AdBlue® dispenser integrated with the fuel management system B.SMART! Starting from today, you can manage the consumption of AdBlue® of your fleet with this new and innovative urea dispenser.

PERFORMANCE

UP TO

32 L/MIN

FLOW RATE

VOLTAGE

AC

POWER

±1%

ACCURACY

NEW

Upgrade your
MC hardware to B.SMART with
KIT UPGRADE SELF SERVICE
1.0/2018

**SELF SERVICE B.SMART**

PACKAGING

CODE	WEIGHT		PACKAGING			N. BOXES / EUROPALET	
	KG	LBS	MM	INCH	PCS/BOX	✈	🚚
FO0748020	48	105	1480X490X400	58.3X19.3X15.7	1		
FO0748050	48	105	1480X490X400	58.3X19.3X15.7	1		
FO0748080	48	105	1480X490X400	58.3X19.3X15.7	1		



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER




WINDSCREEN

CHART



DIMENSIONS



Dimensions expressed in millimeters

IN THE BOX

- SELF SERVICE B.SMART DISPENSER
- DELIVERY HOSE
- SB325_X NOZZLE
- DRIVER ACCESS ADD-ON
- INSTRUCTION MANUAL

DETAILS




3D FILTER



OCIO 2.0 ON REQUEST



B.SMART CLOUD SOFTWARE






B.SMART MOBILE APP

MATERIALS

- **PUMP:**
SUZZARABLU AC PAG. 68
- **METER:**
K24 PAG. 92
- **NOZZLE:**
SB325_X PAG. 114
- **FILTER:**
3D FILTER PAG. 124

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		VOLTAGE			PUMP	METER	NOZZLE	FILTER	INLET	HOSE		
			L/MIN	GPM	AC V./HZ DC VOLT	POWER WATT	AMP. MAX.	TYPE	TYPE	TYPE	3D FILTER	BSP	LENGTH	Ø	
FO0748020	SELF SERV ADBLUE 230V B.SMART 10 ACCESS		34	8,9	230 V	50 HZ	400 W	1.95 A	SUZZARABLUE AC	K24	SB325_X	YES	3/4"	6 M	1"
FO0748050	SELF SERV ADBLUE 230V B.SMART 20 ACCESS		34	8,9	230 V	50 HZ	400 W	1.95 A	SUZZARABLUE AC	K24	SB325_X	YES	3/4"	6 M	1"
FO0748080	SELF SERV ADBLUE 230V B.SMART 50 ACCESS		34	8,9	230 V	50 HZ	400 W	1.95 A	SUZZARABLUE AC	K24	SB325 X	YES	3/4"	6 M	1"

SELF SERVICE B.SMART



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

MCBOX B.SMART

FEATURES

- IDEAL FOR EXISTING PLANTS
- SUITABLE FOR ANY PUMP
- PULSE METER INPUT
- NATIVE WITH B.SMART CLOUD SOFTWARE

MCBOX B.SMART is the new advanced model of the MCBOX AdBlue® control system (electronic control panel that allows you to control any type of AC/DC pump, pulser litre-counter, nozzle and fuel level switches) integrated with the new fuel management and monitoring system PIUSI B.SMART. PIUSI MCBOX B.SMART is suitable for different applications and sectors including agriculture, automotive, logistics, and industry.

PERFORMANCE

VOLTAGE

AC/DC

POWER

UP TO

500

STORABLE

TRANSACTIONS

**MCBOX B.SMART**

PACKAGING

CODE	WEIGHT		PACKAGING		
	KG	LBS	MM	INCH	PCS/BOX
FO0599000	5,2	11,5	300X300X180	11.8X11.8X7.1	1
FO0599040	5,2	11,5	300X300X180	11.8X11.8X7.1	1
FO0599080	5,2	11,5	300X300X180	11.8X11.8X7.1	1
FO0599010	5,4	11,8	300X300X180	11.8X11.8X7.1	1
FO0599050	5,4	11,8	300X300X180	11.8X11.8X7.1	1
FO0599100	5,4	11,8	300X300X180	11.8X11.8X7.1	1
FO0599060	5,4	11,8	300X300X180	11.8X11.8X7.1	1
FO0599070	5,4	11,8	300X300X180	11.8X11.8X7.1	1
FO0599110	5,4	11,8	300X300X180	11.8X11.8X7.1	1



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL



WATER



WINDSCREEN

CONNECTION SCHEME



IN THE BOX

- MCBOX B.SMART
- DRIVER ACCESS ADD-ON
- INSTRUCTION MANUAL

DETAILS



EASY ACCESS TO CONNECTION



OCIO 2.0 ON REQUEST




B.SMART CLOUD SOFTWARE



B.SMART MOBILE APP

DIMENSIONS



Dimensions expressed in millimeters

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	VOLTAGE				B.SMART CLOUD SOFTWARE/APP
			AC VOLT/HZ DC VOLT	AC VOLT/HZ DC VOLT	POWER WATT	AMP. MAX. (load motor)	
FO0599000	MCBOX 100-240V B.SMART 10 ACCESS		100V-240V	50/60 HZ	5 W	15 A	REQUIRED
FO0599040	MCBOX 100-240V B.SMART 20 ACCESS		100V-240V	50/60 HZ	5 W	15 A	REQUIRED
FO0599080	MCBOX 100-240V B.SMART 50 ACCESS		100V-240V	50/60 HZ	5 W	15 A	REQUIRED
FO0599010	MCBOX 12V B.SMART 10 ACCESS		12 V		5 W	50 A	REQUIRED
FO0599050	MCBOX 12V B.SMART 20 ACCESS		12 V		5 W	50 A	REQUIRED
FO0599100	MCBOX 12V B.SMART 50 ACCESS		12 V		5 W	50 A	REQUIRED
FO0599060	MCBOX 24V B.SMART 10 ACCESS		24 V		5 W	25 A	REQUIRED
FO0599070	MCBOX 24V B.SMART 20 ACCESS		24 V		5 W	25 A	REQUIRED
FO0599110	MCBOX 24V B.SMART 50 ACCESS		24 V		5 W	25 A	REQUIRED

MCBOX B.SMART

B.SMART CONTROL BOX

29



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

SSM2.0

FEATURES

- TANK WATCHDOG
- DRIVERS/VEHICLES MANAGEMENT
- REPORT
- SSM 2.0 CLOUD READY
- FLUID INVENTORY VALUE

The SELF SERVICE MANAGEMENT 2.0 software is the response for management and monitoring of refueling, allowing supervision of drivers, vehicles and fuel tanks. Setting up the system and getting to work has never been easier: simply connect the devices to your LAN or Wi-Fi network and click on the "Detect System" button on your PC. SELF SERVICE MANAGEMENT 2.0 will handle the rest. Use of the SELF SERVICE MANAGEMENT 2.0 software requires the new range of SELF SERVICE 2.0 dispensing devices. The ibutton key reader kit is available on request.

PERFORMANCE

UP TO
1000

DRIVERS / VEHICLES

USB/WEBSOFTWARE VERSION
INSTALLATION

SOFTWARE ACTIVATION MODE



**USB
HARDWARE KEY**
without internet
connection



**WEB
EDITION**
internet connection
required





NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL



WATER



WINDSCREEN

CHECK

The cost of the consumption for every distance.

**VIEW**

Bar charts easily allow you to analyze the liters delivered each day and compare them with the average use.

VEHICLES

Reads the average consumption and distance driven.

**TANK MONITORING**

Check the liters delivered over the period you specify.

**TECHNICAL DATA - USB CODE**

CODE	DESCRIPTION
FO0772050	SSM 2.0 ENTRY
FO077202A	SSM 2.0 ADVANCED
FO077204A	SSM 2.0 SUITE
FO0772000	SSM 2.0 CLIENT*

TECHNICAL DATA - WEB CODE

CODE	DESCRIPTION
FO0772250	SSM 2.0 ENTRY - WEB EDITION
FO077222A	SSM 2.0 ADVANCED - WEB EDITION
FO077224A	SSM 2.0 SUITE - WEB EDITION
FO0772200	SSM 2.0 CLIENT* - WEB EDITION

* THE PURCHASE OF ADDITIONAL CLIENT LICENSES ENABLES YOU TO USE THE VARIOUS VERSIONS OF SELF SERVICE MANAGEMENT 2.0 ON MULTIPLE WORKSTATIONS.

SSM2.0

SSM2.0 SOFTWARE

31



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

DATA TRANSFER SSM2.0

Among the equipment related to SSM 2.0, PIUSI has developed a set of technological solutions able to connect the electronic/mechanical device to the fluid control system, that is the software that organizes the operation of the hardware; in this case SELF SERVICE MANAGEMENT 2.0. How does data transfer with SSM2.0 work? It depends on the technology required.

Direct downloading

Use your Manager Key to transfer the data from dispenser to PC: it is enough to touch the dispenser with the key and then use the key reader to transfer the data collected.

LAN/Wi-Fi

The way to receive in real time all information regarding the transactions: using PWLAN or PW Wi-Fi the software recognizes the fuel dispensers and it will automatically send the data to the SELF SERVICE MANAGEMENT 2.0 software.

Mobile Network

The brand-new PW MOBILE 4G 2.0 allows to install dispenser wherever desired, even in the most remote area, without the need of a local network: the device uses the mobile 4G technology to communicate and transfer data and comes with a SIM card included.





NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL



WATER



WINDSCREEN

PW MOBILE



A new communication system that allows you to transfer data using mobile 4G network.

KEY READER & MANAGER KEY 2.0



LAN



A network card that allows the RS485 signal to be converted for connection to a LAN, through a simple and intuitive interface.

PW WI-FI



A device that allows to convert the RS485 signal to Wi-Fi, through a simple and intuitive interface.

TECHNICAL DATA

CODE	DESCRIPTION
F1271012A	PW WIFI 2.0
F12710130	PW MOBILE 4G 2.0
F20552010	MANAGER KEY 2.0
F1226201A	KIT KEY READER

DATA TRANSFER SSM2.0

SSM2.0 SOFTWARE

33



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

SSM2.0 CLOUD

FEATURES

- DATA ALWAYS AVAILABLE
- NO INSTALLATION REQUIRED ON THE PC
- MANAGE SEVERAL SITES AT THE SAME TIME

PIUSI SSM 2.0 CLOUD is the application that lets you control your refueling sites remotely and manage several installations at the same time. With SSM 2.0 CLOUD you can fully monitor the equipment of each site, manage vehicles and drivers, have an overview of the situation of your plants at a glance and filter all data. Information are always available everywhere and at any time thus stored in Cloud.

 **SSM2.0 CLOUD®**

PERFORMANCE

6 MONTHS

FREE TRIAL

TRY&BUY

AVAILABLE DATA

STORAGE

ANYWHERE ANYTIME

DATA BACKUP

**INFO &
CONSUMPTION**

MONITORING

DRIVERS&VEHICLE

TANK LEVEL

MONITORING

TANK WATCHDOG

**NEW**

TRY & BUY

SSM 2.0 CLOUD is now available in the TRY & BUY mode: a free 6-month trial of the CLOUD service made available by PIUSI, which allows you to manage your system from any device or tablet.

Once the free 6-month trial has ended, you can proceed with the purchase keeping in cloud the data used during the trial period.

Ask your dealer for further details!



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL



WATER




WINDSCREEN

TANK WATCHDOG

The tank watchdog section **allows you to manage the level of all your tanks**, mono or multi-site installations.

DASHBOARD

The core of the system. Choose to display the time range you are interested in, group and filter by consumption, dispensing, and levels.



DIVERS&VEHICLES

Add, modify and monitor **the main information of each vehicle and driver** for each of your sites.

DATA BACKUP

Thanks to SSM 2.0 CLOUD all your data are **always backed-up and available anywhere and any time you need**, also in case of PC malfunction.

SITE

Access the "site" section for an **overview of all your sites** and installed devices.

SSM2.0 CLOUD



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

SELF SERVICE MC 2.0

FEATURES

- STURDY STRUCTURE
- ALL-IN-ONE DISPENSER
- BUILT-IN LAN ADAPTER
- FRONT DOOR FOR EASY MAINTENANCE
- SSM 2.0 SOFTWARE REQUIRED
- IP55
- IDEAL FOR FUEL MANAGEMENT

The PIUSI SELF SERVICE MC 2.0 maintains all the advantages of the renown MC system integrated in an AdBlue® dispenser while granting all the 2.0 features: AdBlue® consumption monitoring and report, fleet management, vehicles and users control.

PERFORMANCE

UP TO

32 L/MIN

FLOW RATE

LAN



CONNECTION

±1%

ACCURACY

**SELF SERVICE MC 2.0**

PACKAGING

CODE	WEIGHT		PACKAGING		N. BOXES/EUROPALLET	
	KG	LBS	MM	PCS/BOX		
FO074306A	50	110	1478X488X400	1	6 *	4



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER




WINDSCREEN

CHART



DIMENSIONS



Dimensions expressed in millimeters

IN THE BOX

- SELF SERVICE MC 2.0 DISPENSER
- DELIVERY HOSE
- SB325_X NOZZLE
- INSTRUCTION MANUAL

DETAILS




SSM 2.0 SOFTWARE (PAG. 34)

COMPONENTS

- **PUMP:**
SUZZARABLU PUMP AC PAG. 68
- **METER:**
K24 METER PAG. 92
- **NOZZLE:**
SB325_X PAG. 114
- **FILTER:**
3D FILTER PAG. 124

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		VOLTAGE			METER	NOZZLE	FILTER	INLET	DELIVERY HOSE
			L/MIN	GPM	AC V/HZ DC VOLT	POWER WATT	AMP. MAX.	MOD.	TYPE	3D FILTER	BSP	LENGHT
FO074306A	SELF SERVICE 70 MC 2.0 FOR ADBLUE		32	8,5	230/50	400	1,95	K24	SB325	YES	3/4"	6 M

SELF SERVICE MC 2.0

SSM2.0 DISPENSERS

37



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

MCBOX 2.0

FEATURES

- FLEET MANAGEMENT
- SUITABLE FOR ANY PUMP
- PULSE METER INPUT
- LAN/WI-FI VERSION AVAILABLE
- SSM2.0 SOFTWARE REQUIRED

The PIUSI MCBOX 2.0 is the evolution of the MCBOX system thanks to the integration with the 2.0 features: AdBlue® consumption monitoring and report, fleet management, vehicles and users control. It is suitable to manage and control an existing pump, pulse meter and nozzle.

PERFORMANCE

UP TO
1000

USERS / VEHICLES

AC
VOLTAGE
POWER

**MCBOX 2.0**

PACKAGING

CODE	WEIGHT		PACKAGING		
	KG	LBS	MM	INCH	PCS/BOX
FO059701A	9	19,4	480X370X265	18,9X14,6X10,4	1
FO059702A	5	19,4	480X370X265	18,9X14,6X10,4	1



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL



WATER



WINDSCREEN

CONNECTION SCHEME




IN THE BOX

- MCBOX 2.0 UNIT
- LAN/WI-FI ADAPTER
- INSTRUCTION MANUAL

DETAILS



SHUTTER



USER / VEHICLE KEY




SSM 2.0 SOFTWARE (PAG. 34)



EASY ACCESS TO CONNECTION

DIMENSIONS



Dimensions expressed in millimeters

TECHNICAL DATA

CODICE	DESCRIZIONE	TIPO LIQUIDI	TENSIONE			SOFTWARE SELF-SERVICE MANAGEMENT 2.0
			CA V/Hz	POTENZA W	A MAX (load motor)	
FO059701A	MCBOX LAN 2.0		90-240V - 50/60Hz	35	6,5	REQUIRED
FO059702A	MCBOX WIFI 2.0		90-240V - 50/60Hz	35	6,5	REQUIRED

MCBOX 2.0

SSM2.0 CONTROL BOX

39



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

SSM2018

FEATURES

- **USERS MANAGEMENT**
- **EASY TO INSTALL**
- **TRANSACTION REPORT**

With tens of thousands installations worldwide, PIUSI SELF SERVICE MANAGEMENT 2018 is the benchmark for all entry level FMS to easily monitor your fleet: it allows to monitor all transactions and check reports flexibly. SELF SERVICE MANAGEMENT 2018 allows to continue to work with the Self Service Management 1.0 range, but giving you more potential and more efficiency.

PERFORMANCE

UP TO
16

DISPENSERS

USB/WEB

SOFTWARE VERSION

INSTALLATION

SOFTWARE ACTIVATION MODE



**USB
HARDWARE KEY**
without internet
connection



**WEB
EDITION**
internet connection
required



SELF SERVICE[®]
MANAGEMENT
2018

Software for managing reports
and configuring dispensing
operations.

**1**

ADMINISTER
THE SITE

2

PROCESS
THE REPORTS

3

CONFIGURE
SSM2018



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL



WATER



WINDSCREEN

**MANAGE**

Select or delete the device from your system.



The system min. requirements are:

- Monitor resolution 1280-700
- CPU: Intel® Pentium® 4 or AMD Athlon® 64 processor (2 GHz or higher)
- RAM: 2 GB
- Free space on Hard Disk: 20 GB
- Operating system: Windows VISTA SP2, Windows 7 SP1, Windows 8, Windows 8.1, Windows 10
- Database: Microsoft SQL 2012 R2 SP2 Express (included in the installation)

CHOOSE

Dates, devices, drivers you want a report on.

EXPORT

Your data in the file format you prefer.

**TECHNICAL DATA**

CODE	DESCRIPTION
FOO773010	SELF SERVICE MANAGEMENT 2018 - USB
FOO773210	SELF SERVICE MANAGEMENT 2018 - WEB

SSM2018



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

DATA TRANSFER SSM2018

DATA TRANSFER SSM 2018 is a set of different solutions that let to download the transactions from the dispensers to the SELF SERVICE MANAGEMENT 2018 software. The great variety of the offer is based on the technology required.

Manual download

The easiest way to download the informations is through the Manager key 2018, it is enough to touch the dispenser with the key to transfer all the transactions and download them on the software.

Local network

Use the local network Lan/Wi-Fi to download the dispenser to your pc. By choosing between the PWLAN or PW Wi-Fi it is possible to set up a connection that let you receive all the transactions in real time.

Mobile network

Thanks to the new PW MOBILE 4G 2018 is now possible to install all the dispensers everywhere in the world with just the need of a mobile network coverage, avoiding all the local network configurations. The equipment is provided with a worldwide SIM card which makes the PWMOBILE 4G 2018 ready to use.



PW14 / RS 485

MANAGER KEY
the easiest

PW-LAN

PW-WIFI
wirelessPW-MOBILE
remote, everywhere



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL



WATER



WINDSCREEN

PW14 / RS 485

Connection via
RS485 cable
with USB
converter.

KEY READER & MANAGER KEY**PW LAN**

A device that allows
to convert the RS485 signal
to LAN, through a simple
and intuitive interface.

PW WI-FI

A device that allows
to convert the
RS485 signal to
Wi-Fi, through a
simple and intuitive
interface.

cable max 90 mt

PW MOBILE

A new omuncation
system that allows you
to transfer data using
mobile 4G network.

TECHNICAL DATA

CODE	DESCRIPTION
F1249600A	MANAGER KEY 2018
F1271004B	PW-WIFI
F1271005A	PW-LAN
F12710150	PW MOBILE 4G SS2018
F13292000	PW14 - USB CONVERTER
F12710150	F1226201A

DATA TRANSFER SSM2018

SSM2018 SOFTWARE

43



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

SELF SERVICE MC

FEATURES

- CONTROLLED ACCESS
- BUILT-IN FILTER
- ALL-IN-ONE EQUIPMENT
- COMPACT DESIGN
- SSM2018 SOFTWARE ON REQUEST

The PIUSI SELF SERVICE MC is the combination of the PIUSI MC technology and the Suzzarablu product range. This AdBlue® dispenser is composed of the MC panel, the SUZZARABLU PUMP, the SB325_X nozzle, the K24 pulse meter and 3D FILTER.

PERFORMANCE

UP TO

32 L/MIN

FLOW RATE

UP TO

80

USERS



±1%

ACCURACY



SELF SERVICE MC

PACKAGING

CODE	WEIGHT		PACKAGING		N. BOXES/EUROPALLET	
	KG	LBS	MM	PCS/BOX		
FO074400A	50	110	1478X488X400	1	6*	4



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER




WINDSCREEN

CHART



DIMENSIONS



Dimensions expressed in millimeters

IN THE BOX

- SELF SERVICE MC DISPENSER
- DELIVERY HOSE
- SB325_X NOZZLE
- INSTRUCTION MANUAL

DETAILS



SB325_X NOZZLE



3D FILTER





SSM2018 SOFTWARE (PAG. 34)

COMPONENTS

- PUMP:
SUZZARABLU PUMP AC PAG. 70
- METER:
K24 METER PAG. 92
- NOZZLE:
SB325_X PAG. 114
- FILTER:
3D FILTER PAG. 124

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		VOLTAGE			METER	NOZZLE	FILTER	INLET	DELIVERY HOSE
			L/MIN	GPM	AC V/HZ DC VOLT	POWER WATT	AMP. MAX.	MOD.	TYPE	3D FILTER	BSP	LENGHT
FO074400A	SELF SERVICE 70 MC ADBLUE	 	32	8,5	230/50	400	1,95	K24	SB325	YES	3/4"	6 M

SELF SERVICE MC



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

MCBOX

FEATURES

- ACCESS CONTROL
- SUITABLE FOR ANY PUMP
- PULSE METER INPUT
- EASY TO INSTALL
- MULTI USERS
- COMPATIBLE WITH SSM2018 SOFTWARE

The PIUSI MCBOX is a practical electronic multi-user control panel that allows to manage and control an existing pump, pulse meter and nozzle. Integrated with the SELF SERVICE MANAGEMENT 2018, it grants the possibility to download all the transactions.

PERFORMANCE

UP TO

120

USERS

AC/DC

VOLTAGE

POWER

UP TO

255

TRANSACTION MEMORY

**MCBOX**

PACKAGING

CODE	WEIGHT		PACKAGING		N. BOXES/EUROPALLET	
	KG	LBS	MM	PCS/BOX		
F139800OC	5	19,4	48OX37OX265	1		
F1398005B	5	19,4	48OX37OX265	1		
F1398001B	5	19,4	48OX37OX265	1		
F1398002B	5	19,4	48OX37OX265	1		



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER



WINDSCREEN

CONNECTION SCHEME




IN THE BOX

- MCBOX UNIT
- INSTRUCTION MANUAL

DETAILS



DIMENSIONS



Dimensions expressed in millimeters

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	USERS	VOLTAGE			METERS
				HZ	POWER WATT	AMP. MAX. (load motor)	
F1398000C	MCBOX_230V50/60HZ_80U_IBP		80	50/60 Hz		13	-
F1398005B	MCBOX_230V50/60HZ_120U_IBP		120	50/60 Hz		6,5	-
F1398001B	MCBOX_12V_120U_IBP		120		12V	50	-
F1398002B	MCBOX_24V_120U_IBP		120		24V	25	-

MCBOX

SSM2018 CONTROL BOX


47



FUEL MANAGEMENT SYSTEMS

ACCESSORIES


B.SMART

SELF SERVICE MC B.SMART	CODE	DESCRIPTION
	F00770D00	DRIVER ACCESS (X05)
	F00770D10	DRIVER ACCESS (X15)
	F00770D20	DRIVER ACCESS (X50)
	F1590400A	USER KEY (YELLOW KEY: 10PCS)



F1590400A

F00770D00
F00770D10
F00770D20

MCBOX B.SMART	CODE	DESCRIPTION
	F1270800C	KIT PEDESTAL CUBE BLACK
	F00770D00	DRIVER ACCESS (X05)
	F00770D10	DRIVER ACCESS (X15)
	F00770D20	DRIVER ACCESS (X50)
	F1590400A	USER KEY (YELLOW KEY: 10PCS)
	F1273700A	KIT HANG WALL



F1590400A




F1270800C



F1273700A

F00770D00
F00770D10
F00770D20

SSM2.0


SELF SERVICE MC 2.0	CODE	DESCRIPTION
	F1590400A	KIT DRIVER KEY YELLOW (10PCS)
	F17299000	KIT VEHICLE KEY BLUE (10PCS)



F1590400A



F17299000

MCBOX 2.0	CODE	DESCRIPTION
	F1590400A	KIT DRIVER KEY YELLOW (10PCS)
	F17299000	KIT VEHICLE KEY BLUE (10PCS)




F1590400A



F17299000

SSM2018


SELF SERVICE MC	CODE	DESCRIPTION
	F1590400A	KIT DRIVER KEY YELLOW (10PCS)
	F1249600A	MANAGER KEY 2018



F1590400A



F1249600A

MCBOX	CODE	DESCRIPTION
	F1270800C	KIT PEDESTAL CUBE BLACK
	F1590400A	KIT DRIVER KEY YELLOW (10PCS)
	F17121000	LEVEL PROBE FOR ACCESS 85
	F1249600A	MANAGER KEY 2018
	F1623900B	NOZZLE HOLDER SS+ CABLED SWITCH FM/MC



F1270800C



F1590400A



F1249600A



F1623900B





KITS





CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

SUZZARABLU DRUM

FEATURES

- DESIGNED FOR 200 L DRUM
- EASY TO INSTALL
- SUZZARABLU PUMP

The PIUSI SUZZARABLU DRUM is the solution for all the AdBlue® drum applications. Its adjustable bracket allows an easy installation on any kind of barrel.

PERFORMANCE

UP TO

32 L/MIN

FLOW RATE

AC

VOLTAGE

POWER

20 MIN

DUTY CYCLE

**SUZZARABLU DRUM**

PACKAGING

CODE	WEIGHT		PACKAGING		
	KG	LBS	MM	INCH	PCS/BOX
FOO20135E	16	35,3	470X370X265	18,3X14,6X10,4	1
FOO201D5C	16	35,3	470X370X265	18,3X14,6X10,4	1
FOO201E5C	16	35,3	470X370X265	18,3X14,6X10,4	1



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER




WINDSCREEN

CHART



DIMENSIONS



Dimensions expressed in millimeters

IN THE BOX

- SUZZARABLU DRUM UNIT
- SB325_X / SB325_X METER NOZZLE (ON REQUEST)
- AF2 CONNECTOR
- SUCTION PIPE
- DELIVERY HOSE
- INSTRUCTION MANUAL

DETAILS



SUZZARABLU PUMP AC



AF2 CONNECTOR









SUCTION PIPE

COMPONENTS

- PUMP:
SUZZARABLU PUMP AC PAG. 68
- NOZZLE:
SB325_X METER PAG. 104
SB325_X PAG. 114
SUZZARABLU MANUAL NOZZLE PAG. 118

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		VOLTAGE			METER	NOZZLE	SUCTION	HOSE		ON/OFF
			L/MIN	GPM	AC V./HZ DC VOLT	POWER WATT	AMP. MAX.	MOD.	TYPE		LENGHT	Ø	SWITCH
FOO20135E	SUZZARABLU DRUM 230V/50HZ	 	32	8,5	230/50	400	495	NO	MAN.	AF2	6 M	3/4"	YES
FOO201D5C	SUZZARABLU DRUM 230V/50HZ - SB325_X	 	32	8,5	230/50	400	495	NO	SB325	AF2	6 M	3/4"	YES
FOO201E5C	SUZZARABLU DRUM 230V/50HZ - SB325_X MET	 	32	8,5	230/50	400	495	NO	SB325	AF2	6 M	3/4"	YES

SUZZARABLU DRUM

DRUM

53



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

THREE25

FEATURES

- SPECIFICALLY DESIGNED FOR IBC TANKS
- SUZZARABLU DIAPHRAGM PUMP
- EASY TO INSTALL / REPLACE THE IBC TANK
- AUTOMATIC NOZZLE
- BUILT IN FILTER

PIUSI THREE25 is the most famous AdBlue® dispenser worldwide for IBC tanks. It comes with the SUZZARABLU pump, the SB325_X automatic nozzle, and the 3D FILTER.

PERFORMANCE

UP TO

32 L/MIN

FLOW RATE

AC

VOLTAGE

POWER

6M

HOSE LENGTH

20 MIN

DUTY CYCLE

**THREE25**

PACKAGING

CODE	WEIGHT		PACKAGING		
	KG	LBS	MM	INCH	PCS/BOX
FO0101000	14,5	32	480X390X310	19,3X15,4X12,2	1
FO0101010	14,5	32	480X390X310	19,3X15,4X12,2	1
FO0101020	14,5	32	480X390X310	19,3X15,4X12,2	1
FO0101030	14,5	32	480X390X310	19,3X15,4X12,2	1
FO0101200	14,5	32	480X390X310	19,3X15,4X12,2	1



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER




WINDSCREEN

CHART



DIMENSIONS



Dimensions expressed in millimeters

IN THE BOX

- THREE25 UNIT
- SUCTION / DELIVERY HOSE
- SB325_X NOZZLE
- SEC / AF2 / KIT BOTTOM CONNECTION
- SUCTION DIP TUBE (ONLY AF2 VERSION)
- INSTRUCTION MANUAL

DETAILS



COMPONENTS

- PUMP:
SUZZARABLU PUMP AC PAG. 68
- METER:
K24 METER PAG. 92
- NOZZLE:
SB325_X METER PAG. 104
SB325_X PAG. 114
- FILTER:
3D FILTER PAG. 124

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		VOLTAGE			METER	NOZZLE	SUCTION	SUCTION DIP TUBE	HOSE LENGHT Ø 3/4	ON/OFF SWITCH
			L/MIN	GPM	AC V/HZ DC VOLT	POWER WATT	AMP. MAX.						
FO0101000	PIUSI THREE25 230/50 K24/SB325/SEC	Ad W	32	8,5	230/50	400	1,95	K24	SB325_X	SEC	NO	6 M	YES
FO0101010	PIUSI THREE25 230/50 SB325 MET/SEC	Ad W	32	8,5	230/50	400	1,95	-	SB325_X METER	SEC	NO	6 M	YES
FO0101020	PIUSI THREE25 230/50 K24/SB325/EXT	Ad W	32	8,5	230/50	400	1,95	K24	SB325_X	BOTTOM	NO	6 M	YES
FO0101030	PIUSI THREE25 230/50 SB325_X MET/EXT	Ad W	32	8,5	230/50	400	1,95	-	SB325_X METER	BOTTOM	NO	6 M	YES
FO0101200	PIUSI THREE25 230/50 K24/SB325_X/AF2	Ad W	32	8,5	230/50	400	1,95	K24	SB325_X	AF2	YES	6M	YES

THREE25



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

SUZZARABLU PRO/BASIC

FEATURES

- THE EASIEST SOLUTION FOR IBC
- MANUAL/AUTOMATIC NOZZLE
- SUZZARABLU DIAPHRAGM
- EASY TO INSTALL

The PIUSI SUZZARABLU PRO/BASIC is the first AdBlue® IBC dispenser introduced in the market since 2006. Its sturdy design and practicality makes this product the most common AdBlue® dispenser around the world.

PERFORMANCE

UP TO

35 L/MIN

FLOW RATE

AC/DC

VOLTAGE

POWER

±1%

ACCURACY

20MIN

DUTY CYCLE



SUZZARABLU PRO/BASIC



PACKAGING

CODE	WEIGHT		PACKAGING		
	KG	LBS	MM	INCH	PCS/BOX
FOO201B1B	16	35,3	470X370X265	18,3X14,6X10,4	1
FOO201C9B	16	35,3	470X370X265	18,3X14,6X10,4	1
FOO201BAC	16	35,3	470X370X265	18,3X14,6X10,4	1
FOO201A8B	12,6	27,8	470X370X265	18,3X14,6X10,4	1
FOO201B2B	16	35,3	470X370X265	18,3X14,6X10,4	1
FOO201E8B	16	35,3	470X370X265	18,3X14,6X10,4	1
FOO201A9B	12,6	27,8	470X370X265	18,3X14,6X10,4	1



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER




WINDSCREEN

CHART



DIMENSIONS



Dimensions expressed in millimeters

IN THE BOX

- SUZZARABLU AC/DC UNIT
- MANUAL NOZZLE / AUTO NOZZLE (PRO VERSION)
- FLOW METER (ON REQUEST)
- SUCTION / DELIVERY HOSE
- SEC / KIT BOTTOM CONNECTION
- INSTRUCTION MANUAL

DETAILS



DC VERSION AVAILABLE



KIT BOTTOM AVAILABLE



K24 METER



CART KIT AVAILABLE (PAG.64)

COMPONENTS

- PUMPS:
SUZZARABLU PUMP AC PAG. 68
SUZZARABLU PUMP DC PAG. 70
- METER:
K24 METER PAG. 92
- NOZZLE:
SB325_X METER PAG. 104
SB325_X PAG. 114
SUZZARABLU A60 PAG. 116
SUZZARABLU MANUAL NOZZLE PAG. 118

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		VOLTAGE			METER	NOZZLE	SUCTION	HOSE LENGHT Ø 3/4"	ON/OFF SWITCH
			L/MIN	GPM	AC V./HZ DC VOLT	POWER WATT	AMP. MAX.					
FOO201B1B	SUZZARABLU PRO 230V/50HZ K24 W/SEC	AdBlue®	32	8,5	230/50	400	1,95	YES	A60	SEC	6 M	YES
FOO201C9B	SUZZARABLU PRO K24 230V/50HZ SB325_X	AdBlue®	32	8,5	230/50	400	1,95	YES	SB325	SEC	6 M	YES
FOO201BAC	SUZZARABLU PRO K24 SB325_X - EXT SUCT	AdBlue®	32	8,5	230/50	400	1,95	YES	SB325	BOTTOM	6 M	YES
FOO201A8B	SUZZARABLU PRO K24 12V	AdBlue®	35	9,2	12	260	22	YES	A60.	-	6 M	YES
FOO201B2B	SUZZARA BLUE BASIC 230V/50HZ W/SEC	AdBlue®	32	8,5	230/50	400	1,95	NO	MAN.	SEC	6 M	YES
FOO201E8B	SUZZARABLU BASIC 230V/50HZ SB325_X W/SEC	AdBlue®	32	8,5	230/50	400	1,95	NO	SB325	SEC	6 M	YES
FOO201A9B	SUZZARABLU BASIC 12V	AdBlue®	35	9,2	12	260	22	NO	MAN.	-	6 M	YES

SUZZARABLU PRO/BASIC



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

SUZZARABLU PORTABLE KIT

FEATURES

- **READY TO USE**
- **TRANSPORTABLE**
- **CLAMPS FOR BATTERY CONNECTION**

Ease of use is the main feature of the PIUSI SUZZARABLU PORTABLE KIT. The basic version of all Adblue® dispensers: it is composed by the SUZZARABLU PUMP and SUZZARABLU MANUAL NOZZLE.

PERFORMANCE

UP TO

35 L/MIN

FLOW RATE

AC/DC

VOLTAGE

POWER

20 MIN



DUTY CYCLE



SUZZARABLU PORTABLE KIT



PACKAGING

CODE	WEIGHT		PACKAGING		N. BOXES / EUROPALLET	
	KG	LBS	MM	PCS/BOX		
FOO201AAA	8	17,6	357X327X275	1	24	36
FOO201C7A	10	22	357X327X275	1	24	36



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIO DIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER




WINDSCREEN

CHART



DIMENSIONS



Dimensions expressed in millimeters

IN THE BOX

- SUZZARABLU PUMP AC/DC
- MANUAL NOZZLE
- FOOT VALVE
- SUCTION/DELIVERY HOSE
- INSTRUCTION MANUAL

DETAILS



COMPONENTS

- PUMP:
SUZZARABLU PUMP AC PAG. 68
SUZZARABLU PUMP DC PAG. 70
- NOZZLE:
SUZZARABLU MANUAL NOZZLE PAG. 118

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		VOLTAGE			NOZZLE	HOSE		ON/OFF
			L/MIN	GPM	AC V/Hz DC VOLT	POWER WATT	AMP. MAX.	TYPE	LENGHT	Ø	SWITCH
FOO201AAA	SUZZARABLU KIT 12V	Ad W	35	9,2	12	260	22	MANUAL	6 M	3/4"	YES
FOO201C7A	SUZZARABLU KIT 230 V	Ad W	32	8,5	230/50	400	1,95	MANUAL	6 M	3/4"	YES

SUZZARABLU PORTABLE KIT

MOBILE

59



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

PIUSIBOX FOR ADBLUE®

FEATURES

- PORTABLE
- EASY TO HANDLE
- READY TO USE
- SEC CONNECTION ADAPTER
- DESIGNED FOR HEAVY DUTY APPLICATIONS

PERFORMANCE

UP TO

35 L/MIN

FLOW RATE

DC**VOLTAGE**

POWER

20 MIN

DUTY CYCLE



PIUSIBOX FOR ADBLUE®



PACKAGING

CODE	WEIGHT		PACKAGING		
	KG	LBS	MM	INCH	PCS/BOX
FO0204060	16	35,3	650X400X450	25,6X15X17,7	1



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER




WINDSCREEN

CHART



DIMENSIONS



Dimensions expressed in millimeters

IN THE BOX

- SUZZARABLU PUMP DC
- AUTOMATIC NOZZLE
- SUCTION / DELIVERY HOSE
- INSTRUCTION MANUAL

DETAILS



NOZZLE



SEC CONNECTOR INCLUDED



WHEELS

COMPONENTS

- PUMP:
SUZZARABLU PUMP DC PAG. 70
- NOZZLE:
SB325_X PAG. 114

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		VOLTAGE			RPM	DUTY CYCLE	CABLE	NOZZLE	DELIVERY HOSE	SEC	GLOVES
			L/MIN	GPM	AC V/Hz	DC VOLT	POWER WATT				TYPE	LENGHT		
FO0204060	PIUSIBOX FOR ADBLUE	Ad W	35	9,2	24		310	13	2800	20	YES	SB325 6 M	YES	YES

PIUSIBOX FOR ADBLUE®

MOBILE

61



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

SUZZARABLU BOX

FEATURES

- EASY TO INSTALL
- READY TO USE
- BUILT-IN LOCK

The PIUSI SUZZARABLU BOX is specifically designed for wall or tank installation. Is is equipped with a metallic box which allows to lock up all the equipment.

PERFORMANCE

UP TO

32 L/MIN

FLOW RATE

AC

VOLTAGE

POWER

±1%

ACCURACY

20 MIN

DUTY CYCLE

**SUZZARABLU BOX**

PACKAGING

CODE	WEIGHT		PACKAGING		
	KG	LBS	MM	INCH	PCS/BOX
FOO20196B	25	55,1	575X320X607	22,6X23,9	1



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER




WINDSCREEN

CHART



DIMENSIONS



Dimensions expressed in millimeters

IN THE BOX

- SUZZARABLU PUMP AC
- K24 METER
- NOZZLE
- INSTRUCTION MANUAL



DETAILS



COMPONENTS

- PUMP:
SUZZARABLU PUMP AC PAG. 68
- METER:
K24 METER PAG. 92
- NOZZLE:
SUZZARABLU A60 PAG. 116

TECHNICAL DATA


CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		VOLTAGE			METER	NOZZLE	HOSE LENGTH
			L/MIN	GPM	AC V/HZ DC VOLT	POWER WATT	AMP. MAX.	MOD.	TYPE	
FOO20196B	SUZZARABLU BOX	 	32	8,5	230/50	400	1,95	K24	SUZZARABLU NOZZLE A60	6 M

SUZZARABLU BOX




KITS ACCESSORIES

DRUM

SUZZARABLU DRUM	CODE	DESCRIPTION
	F20189000	AF2 56X4 BUTTRESS - 1" BSP
	F20190000	AF2 2" BUTTRESS - 1" BSP
	F20257000	AF2 2" BSP - 1" BSP
	F20258000	AF2 2" 70X6 - 1" BSP

F20189000 / F20190000
F20257000 / F20258000


IBC

THREE25	CODE	DESCRIPTION
	F15452000	SEC + HOSETAIL 90°
	F1206801B	SUZZARABLU CART KIT
	F15606000	KIT RIGID SUCTION HOSE SUZZARA BLUE DRUM

F15452000

F1206801B

F15606000


SUZZARABLU PRO/BASIC	CODE	DESCRIPTION
	F15452000	SEC + HOSETAIL 90°
	F1206801B	SUZZARABLU CART KIT
	F15606000	KIT RIGID SUCTION HOSE SUZZARA BLUE DRUM

F15452000

F1206801B

F15606000

ST

SUZZARABLU BOX	CODE	DESCRIPTION
	F1611800D	KIT COMPLETE BOX FOR SUZZARABLU BOX
	F20300000	PLATE SUZZ.BLU BOX - PEDESTAL CUBE
	F1270800C	KIT PEDESTAL CUBE BLACK

F1270800C

F20300000

F1611800D





PUMPS

A large, solid red triangle is positioned in the bottom right corner of the page, pointing towards the top right.



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

SUZZARABLU PUMP AC

FEATURES

- **READY TO USE**
- **MULTI-PURPOSE PUMP**
- **SELF PRIMING**
- **BUILT-IN BYPASS VALVE**

The PIUSI SUZZARABLU PUMP AC is the most famous diaphragm pump for AdBlue®. It is equipped with electric motor without any dynamic seals. This solution allows to obtain a reliable industrial pump together with self priming capabilities.

PERFORMANCE

UP TO

32 L/MIN


FLOW RATE

20 MIN

DUTY CYCLE

**SUZZARABLU PUMP AC**

PACKAGING

CODE	WEIGHT		PACKAGING		N. BOXES/EUROPALLET	
	KG	LBS	MM	PCS/BOX		
FO0203090	7	15,4	350X180X280	1	60	84



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER



WINDSCREEN

CHART



IN THE BOX

- SUZZARABLU PUMP AC
- HOSE FITTINGS
- INSTRUCTION MANUAL

DETAILS




ON/OFF SWITCH



FIXING PLATE

DIMENSIONS



Dimensions expressed in millimeters

MATERIALS

- BODY: POLIPROPYLENE
- DIAPHRAGM: POLIPROPYLENE

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		VOLTAGE				CABLES	INLET-OUTLET	ON/OFF
			L/MIN	GPM	AC V/HZ DC VOLT	RPM	POWER WATT	AMP. MAX.	MOD.	BSP	SWITCH
FOO203090	SUZZARABLU AC PUMP 230/50	Ad W	32	8,5	230/50	1450	400	1,95	YES	3/4"	YES

UPON REQUEST IT IS AVAILABLE WITH DIFFERENT VOLTAGE AND FREQUENCY.

SUZZARABLU PUMP AC

AC PUMP

69



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

SUZZARABLUE PUMP DC

FEATURES

- **READY TO USE**
- **MULTI-PURPOSE PUMP**
- **SELF PRIMING**
- **BUILT-IN BYPASS VALVE**

The PIUSI SUZZARABLUE PUMP DC is an electric DC diaphragm pump suitable for transferring AdBlue®. This self-priming pump is equipped with a built-in pressure by-pass.

PERFORMANCE

UP TO

35 L/MIN

FLOW RATE

20 MIN



DUTY CYCLE



SUZZARABLUE PUMP DC



PACKAGING

CODE	WEIGHT		PACKAGING		N. BOXES/EUROPALLET	
	KG	LBS	MM	PCS/BOX		
FO0204080	3,6	7,9	350X180X280	1	60	84
FO0204090	3,6	7,9	350X180X280	1	60	84



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER




WINDSCREEN

CHART



DIMENSIONS



Dimensions expressed in millimeters

IN THE BOX

- SUZZARABLU PUMP DC
- CLAMPS
- INSTRUCTION MANUAL

DETAILS



MATERIALS

- BODY: POLIPROPYLENE
- DIAPHRAGM: POLIPROPYLENE

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		VOLTAGE				CABLES	INLET-OUTLET	ON/OFF
			L/MIN	GPM	AC V/HZ DC VOLT	RPM	POWER WATT	AMP. MAX.	MOD.	BSP	SWITCH
FOO204080	SUZZARABLU DC PUMP 12V	Ad W	35	9,2	12	2800	260	22	YES	3/4"	YES
FOO204090	SUZZARABLU DC PUMP 24V	Ad W	35	9,2	24	2800	310	13	YES	3/4"	YES

SUZZARABLU PUMP DC

DC PUMP

71



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

SQUALO35

FEATURES

- **HEAVY DUTY**
- **REGENERATIVE TURBINE**
- **INTEGRATED PRESSURE REGULATOR**
- **BUILT-IN NON RETURN VALVE**

SQUALO35 is the first submersible pump for AdBlue® to have been especially developed and tested for distribution systems. A centrifugal pump fitted with a turbine regenerator with non-return valve and a built-in innovative pressure regulation system that optimises flow rate performance levels. Consistent flow rate and accuracy during delivery dramatically reduce energy consumption levels. The compact size and special pump design make for easy installation and near-complete emptying of the intended installation tank.

PERFORMANCE

UP TO

35 L/MIN

FLOW RATE

AC**VOLTAGE**

POWER

30 MM

DEAD LEVEL

**SQUALO35**

PACKAGING

CODE	WEIGHT		PACKAGING		
	KG	LBS	MM	INCH	PCS/BOX
FO0206010	7	15,4	510X240X150	20X9,4X5,6	1
FO0206020	7	15,4	510X240X150	20X9,4X5,6	1



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER




WINDSCREEN

CHART



DIMENSIONS



Dimensions expressed in millimeters


IN THE BOX

- SQUALO35
- INSTRUCTION MANUAL

DETAILS



MESH STRAINER



5 METERS POWER CORD



BUILT-IN NON RETURN VALVE



PRESSURE EQUALIZER

MATERIALS

- BODY: STAINLESS STEEL/TECHNOPOLYMER
- TURBINE: TECHNOPOLYMER

TECHNICAL DATA

CODICE	DESCRIPTION	FLUIDS TYPE	WORKING PRESSURE	FLOW RATE		VOLTAGE		DEAD LEVEL	POWER CORD
				L/MIN	GPM	CA V/HZ CC V	WATT		
FOO206010	SQUALO35 230/50 BASIC		1,8 BAR 27 PSI	35	7,7	230/50	560	30MM	5 M
FOO206020	SQUALO35 230/50 TIMER		1,8 BAR 27 PSI	35	7,7	230/50	560	30 MM	5 M

SQUALO35

SUBMERSIBLE PUMP

73



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

MP 130

FEATURES

- IN/OUT INTERCHANGEABLE
- BUILT-IN DIFFUSER
- SUITABLE FOR SUBMERSIBLE INSTALLATION
- HEAVY DUTY
- EASY TO FIT
- STURDY DESIGN

PERFORMANCE

UP TO

50 L/MIN

FLOW RATE

MAX CAPACITY

5M

SELF PRIMING

MAX

7 BAR

AIR SUPPLY

PRESSURE

MAX

Ø 4MM

PASSING SOLID

The PIUSI MP 130 is a pneumatic diaphragm pump suitable for transferring AdBlue®. Thanks to its small size, this pump is easy to fit. It is self-priming and it can run dry without damage.

**MP 130**

PACKAGING

CODE	WEIGHT		PACKAGING		
	KG	LBS	MM	INCH	PCS/BOX
FOO208POO	3,6	7,9	220X310X320	8,7X12X12,6	1



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER



WINDSCREEN

CHART



IN THE BOX

- MP 130 PUMP
- INSTRUCTION MANUAL

DETAILS



HEAVY DUTY MATERIALS




TECHNOPOLYMER BODY



STURDY DESIGN

DIMENSIONS



Dimensions expressed in millimeters

MATERIALS

- BODY: TECHNOPOLYMER
- SIDE PARTS AND COLLECTORS: POLYPROPYLENE
- DIAPHRAGM: EPDM

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	PUMP BODY	IN / OUT	FLOW RATE	MEMBRANE TYPE	DIAPHRAGM AIR SIDE / FLUID SIDE	BALLS	BALL SEATS*	O-RING*	INTAKE / DELIVERY CONNECTION	AIR CONNECTION	MAX SELF-PRIMING CAPACITY	MAX HEAD**	MAX AIR SUPPLY PRESSURE	MAX Ø OF PASSING SOLID
					L/MIN								M	M	BAR	MM
FOO208POO	PIUSI MP 130		POLYPROPYLENE	1/2" G	50	DOUBLE	PTFE / HYTREL	PTFE	POLYPROPYLENE	PTFE	G 1/2" F	G 3/8" F	5	70	7	4

(*) ON REQUEST WE CAN PROVIDE MEMBRANES, BALLS, BALL SEATS AND O-RINGS IN DIFFERENT MATERIALS.

(**) THE VALUE DEPENDS ON THE CONFIGURATION OF THE PUMP

MP 130



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

MP 140

FEATURES

- IN/OUT INTERCHANGEABLE
- BUILT-IN DIFFUSER
- SUITABLE FOR SUBMERSIBLE INSTALLATION
- HEAVY DUTY
- EASY TO FIT
- STURDY DESIGN

PERFORMANCE

UP TO

100 L/MIN

FLOW RATE

MAX CAPACITY

6M

SELF PRIMING

MAX

7 BAR

AIR SUPPLY

PRESSURE

MAX

Ø 4MM

PASSING SOLID

The PIUSI MP 140 is a long-lasting pneumatic diaphragm pump suitable for transferring AdBlue®. The small size of this pump allows a wide range of installations, even in severe duty conditions.

**MP 140**

PACKAGING

CODE	WEIGHT		PACKAGING		
	KG	LBS	MM	INCH	PCS/BOX
FO0208P20	5	11	240X380X350	9,4X15X13,8	1



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER



WINDSCREEN

CHART



IN THE BOX

- MP 140 PUMP
- INSTRUCTION MANUAL

DETAILS



HEAVY DUTY MATERIALS




TECHNOPOLYMER BODY



STURDY DESIGN

DIMENSIONS



Dimensions expressed in millimeters

MATERIALS

- BODY: TECHNOPOLYMER
- SIDE PARTS AND COLLECTORS: POLYPROPYLENE
- DIAPHRAGM: EPDM

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	PUMP BODY	IN / OUT	FLOW RATE	MEMBRANE TYPE	DIAPHRAGM AIR SIDE / FLUID SIDE	BALLS	BALL SEATS*	O-RING*	INTAKE / DELIVERY CONNECTION	AIR CONNECTION	MAX SELF-PRIMING CAPACITY	MAX HEAD**	MAX AIR SUPPLY PRESSURE	MAX Ø OF PASSING SOLID
					L/MIN								M	M	BAR	MM
FOO208P20	PIUSI MP 140		POLYPROPYLENE	1" G	100	DOUBLE	PTFE / HYTREL	PTFE	POLYPROPYLENE	PTFE	G 1" F	G 3/8" F	6	70	7	4

(*) ON REQUEST WE CAN PROVIDE MEMBRANES, BALLS, BALL SEATS AND O-RINGS IN DIFFERENT MATERIALS.

(**) THE VALUE DEPENDS ON THE CONFIGURATION OF THE PUMP

MP 140



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

MP 180

FEATURES

- IN/OUT INTERCHANGEABLE
- LONG LIFE DIAPHRAGM
- BUILT-IN DIFFUSER
- SUITABLE FOR SUBMERSIBLE INSTALLATIONS
- MULTI-PURPOSE PUMP
- STURDY DESIGN

The PIUSI MP 180 is a long-lasting pneumatic diaphragm pump suitable for an heavy duty usage. Thanks to its characteristics, this multi-purpose pump allows a range of wide installations including potentially explosive conditions.

PERFORMANCE

UP TO

150 L/MIN

FLOW RATE

MAX CAPACITY

5M

SELF PRIMING

MAX

7 BAR

AIR SUPPLY

PRESSURE

MAX

Ø 4MM

PASSING SOLID

**MP 180**

PACKAGING

CODE	WEIGHT		PACKAGING		
	KG	LBS	MM	INCH	PCS/BOX
FOO208P30	7,5	16,5	270X390X400	10,6X15,4X15,7	1



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER



WINDSCREEN

CHART



IN THE BOX

- MP 180 PUMP
- INSTRUCTION MANUAL

DETAILS



HEAVY DUTY MATERIALS




TECHNOPOLYMER BODY



STURDY DESIGN

DIMENSIONS



Dimensions expressed in millimeters

MATERIALS

- BODY: TECHNOPOLYMER
- SIDE PARTS AND COLLECTORS: POLYPROPYLENE
- DIAPHRAGM: EPDM

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	PUMP BODY	IN / OUT	FLOW RATE	MEMBRANE TYPE	DIAPHRAGM AIR SIDE / FLUID SIDE	BALLS	BALL SEATS*	O-RING*	INTAKE / DELIVERY CONNECTION	AIR CONNECTION	MAX SELF-PRIMING CAPACITY	MAX HEAD**	MAX AIR SUPPLY PRESSURE	MAX Ø OF PASSING SOLID
					L/MIN								M	M	BAR	MM
FOO208P30	PIUSI MP 180		POLYPROPYLENE	1" G	150	DOUBLE	PTFE / HYTREL	PTFE	POLYPROPYLENE	PTFE	G 1" F	G 3/8" F	5	70	7	4

(*) ON REQUEST WE CAN PROVIDE MEMBRANES, BALLS, BALL SEATS AND O-RINGS IN DIFFERENT MATERIALS.

(**) THE VALUE DEPENDS ON THE CONFIGURATION OF THE PUMP

MP 180



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

MP 190

FEATURES

- IN/OUT INTERCHANGEABLE
- LONG LIFE DIAPHRAGM
- BUILT-IN DIFFUSER
- SUITABLE FOR SUBMERSIBLE INSTALLATIONS
- HEAVY DUTY
- MULTI-PURPOSE PUMP
- STURDY DESIGN

PERFORMANCE

UP TO

220 L/MIN

FLOW RATE

MAX CAPACITY

6M

SELF PRIMING

MAX

7 BAR

AIR SUPPLY


PRESSURE

MAX

Ø 4MM

PASSING SOLID

The PIUSI MP 190 is a pneumatic multi-purpose AdBlue® diaphragm pump. The sturdy central technopolymer body makes this pump suitable for an heavy duty usage.

**MP 190**

PACKAGING

CODE	WEIGHT		PACKAGING		
	KG	LBS	MM	INCH	PCS/BOX
FOO208P40	12	26,5	290X470X460	11,4X18,5X18,1	1



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER



WINDSCREEN

CHART



IN THE BOX

- MP 190 PUMP
- INSTRUCTION MANUAL

DETAILS



HEAVY DUTY MATERIALS




TECHNOPOLYMER BODY



STURDY DESIGN

DIMENSIONS



Dimensions expressed in millimeters

MATERIALS

- BODY: TECHNOPOLYMER
- SIDE PARTS AND COLLECTORS: POLYPROPYLENE
- DIAPHRAGM: EPDM

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	PUMP BODY	IN / OUT	FLOW RATE	MEMBRANE TYPE	DIAPHRAGM AIR SIDE / FLUID SIDE	BALLS	BALL SEATS*	O-RING*	INTAKE / DELIVERY CONNECTION	AIR CONNECTION	MAX SELF-PRIMING CAPACITY	MAX HEAD**	MAX AIR SUPPLY PRESSURE	MAX Ø OF PASSING SOLID
					L/MIN								M	M	BAR	MM
FOO208P40	PIUSI MP 190		POLYPROPYLENE	1" 1/4" G	220	DOUBLE	PTFE / HYTREL	PTFE	POLYPROPYLENE	PTFE	G 1/4" F	G 1/2" F	6	70	7	4

(*) ON REQUEST WE CAN PROVIDE MEMBRANES, BALLS, BALL SEATS AND O-RINGS IN DIFFERENT MATERIALS.

(**) THE VALUE DEPENDS ON THE CONFIGURATION OF THE PUMP

MP 190



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

PIUSI HAND PUMP

FEATURES

- STURDY CONNECTOR
- HEAVY DUTY LEVER
- HIGH EFFICIENCY
- ADJUSTABLE SUCTION PIPE
- SELECTED MATERIALS
- BUILT-IN NON RETURN VALVE

The PIUSI HAND PUMP is a rotary vane pump suitable for transferring AdBlue®. Entirely designed, manufactured and certified in Italy, this sturdy pump guarantees a professional performance and it is indicated for all drum applications.

PERFORMANCE

UP TO

38 L

PER 100 REV.

FLOW RATE

**PIUSI HAND PUMP**

PACKAGING

CODE	WEIGHT		PACKAGING		N. BOXES/EUROPALLET	
	KG	LBS	MM	PCS/BOX		

WITHOUT HOSE

FO0332A0A	2,1	4,6	350X170X140	1	50	100
FO0332A1A	2,1	4,6	350X170X140	1	50	100
FO0332A4A	2,1	4,6	350X170X140	1	50	100
FO0332A6A	2,1	4,6	350X170X140	1	50	100

WITH HOSE

FO0332A2A	3,2	7	300X300X180	1	50	100
FO0332A8A	3,2	7	300X300X180	1	50	100
FO0332A5A	3,2	7	300X300X180	1	50	100
FO0332A7A	3,2	7	300X300X180	1	50	100
FO0332A9A	3,2	7	300X300X180	1	50	100



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER




WINDSCREEN

CHART



DIMENSIONS



Dimensions expressed in millimeters

IN THE BOX

- PIUSI HAND PUMP
- DRUM CONNECTOR
- SUCTION PIPE
- DELIVERY HOSE
- INSTRUCTION MANUAL

DETAILS



DRUM CONNECTOR



SUCTION PIPE






























STAINLESS STEEL SPOUT

MATERIALS

- BODY: STAINLESS STEEL/TECHNOPOLYMER
- ROTOR: TECHNOPOLYMER
- VANES: TECHNOPOLYMER

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	3D FILTER INCLUDED	CAPACITY PER 100 REVOLUTIONS		DRUM CONNECTOR	SUCTION TUBE	DELIVERY HOSE LENGHT
				L	USG			M
WITHOUT HOSE								
FOO332A0A	PIUSI HAND PUMP 56X4	  	NO	38	10	56X4	YES	-
FOO332A1A	PIUSI HAND PUMP UREA 2" BUT.	  	NO	38	10	2" BUTTRESS	YES	-
FOO332A4A	PIUSI HAND PUMP UREA 2" BSP	  	NO	38	10	2" BSP	YES	-
FOO332A6A	PIUSI HAND PUMP UREA 70X6	  	NO	38	10	70X6	YES	-
WITH HOSE								
FOO332A2A	PIUSI HAND PUMP UREA 56X4 W/HOSE	  	NO	38	10	56X4	YES	2,5
FOO332A8A	PIUSI HAND PUMP UREA 2" BUT. W/H F	  	YES	38	10	2" BUTTRESS	YES	2,5
FOO332A5A	PIUSI HAND PUMP UREA 2" BSP W/HOSE	  	NO	38	10	2" BSP	YES	2,5
FOO332A7A	PIUSI HAND PUMP UREA 70X6 W/HOSE	  	NO	38	10	70X6	YES	2,5
FOO332A9A	PIUSI HAND PUMP UREA 56X4 70X6 2"BSP W/H	  	NO	38	10	2" BSP	YES	2,5

PIUSI HAND PUMP

HAND PUMPS

83



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

PIUSI HAND PUMP IBC

FEATURES

- IBC ERGONOMIC BRACKET
- HEAVY DUTY LEVER
- HIGH EFFICIENCY
- SELECTED MATERIALS

The PIUSI HAND PUMP IBC is a rotary vane pump suitable for transferring AdBlue®. It maintains all the main features of the PIUSI HAND PUMP while its ergonomic bracket guarantees a perfect IBC handling.

PERFORMANCE

UP TO

38 L

PER 100 REV

FLOW RATE

**PIUSI HAND PUMP IBC**

PACKAGING

CODE	WEIGHT		PACKAGING		
	KG	LBS	MM	INCH	PCS/BOX
WITHOUT FILTER					
FOO332BOA	2,1	4,6	350X170X5,5	13,8X6,7X5,5	1
WITH FILTER					
FOO332B1A	3,2	7	300X300X180	18,8X11,8X7,1	1



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER




WINDSCREEN

CHART



DIMENSIONS



Dimensions expressed in millimeters

IN THE BOX

- PIUSI HAND PUMP IBC
- IBC MOUNT BRACKET
- DELIVERY HOSE
- 3D FILTER (ON REQUEST)
- INSTRUCTION MANUAL

DETAILS



STAINLESS STEEL SPOUT



STURDY LEVER









IBC BRACKET

MATERIALS

- BODY: STAINLESS STEEL, TECHNOPOLYMER
- ROTOR: TECHNOPOLYMER
- VANES: TECHNOPOLYMER

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	CAPACITY PER 100 REVOLUTIONS		IBC BRAKET	SUCTION HOSE	DELIVERY HOSE LENGTH	3D FILTER
			L	USG	MOD.	M	M	
WITHOUT FILTER								
FOO332BOA	PIUSI HAND PUMP FOR IBC W/O FILTER	  	38	10	YES	1	2,5	NO
WITH FILTER								
FOO332B1A	PIUSI HAND PUMP UREA SIDE W/FILTER	  	38	10	YES	1	2,5	YES

IBC NOT INCLUDED

PIUSI HAND PUMP IBC

HAND PUMPS

85



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

SUZZARABLU HAND PUMP

FEATURES

- READY / EASY TO USE
- SUITABLE FOR ANY OPERATING CONDITION

The PIUSI SUZZARABLU HAND PUMP is the basic version of hand pump (piston) offered by PIUSI. They are manufactured in plastic according to the ISO 22241.

PERFORMANCE

3M

HOSE LENGTH



SUZZARABLU HAND PUMP



PACKAGING

CODE	WEIGHT		PACKAGING		N. BOXES/EUROPALLET	
	KG	LBS	MM	PCS/BOX		

PISTON HAND PUMPS

FO033209A	1,5	3,3	16OX34OX14O	1	72	102
FO033210A	3,4	7,5	51OX24OX15O	1	48	66



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER



WINDSCREEN

CHART



Dimensions expressed in millimeters

IN THE BOX

- SUZZARABLU HAND PUMP
- DELIVERY HOSE (ON REQUEST)
- SUCTION PIPE
- INSTRUCTION MANUAL

DETAILS



LEVER









SPOUT

MATERIALS

- BODY: PLASTIC
- ROTOR: PLASTIC
- VANES: PLASTIC

TECHNICAL DATA


TECHNICAL DATA								
CODE	DESCRIPTION	FLUIDS TYPE	SPOUT	HOSE		DIP PIPE	COMPLETE KIT	MAUSER AND GREIF ADAPTER FOR DRUM
			BSP	LENGHT	Ø			
PISTON HAND PUMP								
FOO33209A	PISTON HAND PUMP (WITH DIP PIPE)	  	3/4"	-	-	YES	-	-
FOO33210A	PISTON HAND PUMP (WITH COMPLETE KIT)	  	3/4"	3 M	3/4"	YES	YES	YES

SUZZARABLU HAND PUMP



PUMPS ACCESSORIES


DC PUMP

SUZZARABLU PUMP DC	CODE	DESCRIPTION
	R16175010	KIT HANDLE



R16175010

HAND PUMPS

PIUSI HAND PUMP	CODE	DESCRIPTION
	FOO611DOO	3D FILTER + HOUSING
	R1512800A	ADAPTER M/F 2" - S7OX6 ADBLUE
	F19158000	DRUM CONNECTOR 56X4
	F19159000	DRUM CONNECTOR 2" BUTTRESS
	F19157000	DRUM CONNECTOR 2" BSP
	F19157010	DRUM CONNECTOR 70X6




FOO611DOO



F19158000 / F19159000
F19157010 / F19157000



R1512800A

PIUSI HAND PUMP IBC	CODE	DESCRIPTION
	F20189000	AF2 56X4 BUTTRESS - 1" BSP
	F20190000	AF2 2" BUTTRESS - 1" BSP
	F20257000	AF2 2" BSP - 1" BSP
	F20258000	AF2 2" 70X6 - 1" BSP
	F15452000	SEC + HOSETAIL 90°
	F15515000	EXT SUCTION HOSE IBC TANK W/FOOT VALVE
	F15606000	KIT RIGID SUCTION HOSE SUZZARA BLUE DRUM
	FOO611DOO	3D FILTER + HOUSING
	F15236000	ADATTATORE M/F 2IN - 56X4 ADBLUE



F20189000 / F20190000
F20257000 / F20258000



F15606000



F15452000




FOO611DOO



F15515000




F15236000

SUZZARABLU HAND PUMP	CODE	DESCRIPTION
	R1512800A	ADAPTER M/F 2" - S7OX6 ADBLUE
	F15236000	ADATTATORE M/F 2IN - 56X4 ADBLUE



R1512800A
F15236000





METERS





CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

K24

FEATURES

- FLOW RATE INDICATION
- STANDARD AAA BATTERIES
- ROTABLE DISPLAY
- LOW BATTERY CONSUMPTION
- RUBBER PROTECTION

PERFORMANCE

UP TO 120 L/MIN	10 BAR MAX
FLOW RATE	OPERATING PRESSURE
±1%	0,3%
ACCURACY	REPEATABILITY

The K24 is PIUSI's exclusive turbine meter. Its compact design, accuracy and ease of use makes this flow meter an excellence in measuring AdBlue®. It is equipped with a compact and easy readable display that can be rotated in 4 different positions.

**K24****K24 PULSE METER**

PACKAGING

CODE	WEIGHT		PACKAGING		
	KG	LBS	MM	INCH	PCS/BOX
FOO40710A	0,4	0,9	BLISTER	BLISTER	1
FOO40721B	0,4	0,9	115X160X135	4,5X3X5,3	1



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER



WINDSCREEN

CHART



IN THE BOX

- K24 METER
- STAINLESS STEEL SOCKET
- INSTRUCTION MANUAL

DETAILS




ROTABLE DISPLAY



TURBINE

DIMENSIONS



Dimensions expressed in millimeters

MATERIALS

- BODY: TECHNOPOLYMER
- TURBINE: TECHNOPOLYMER

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		PRESSURE		DISPLAY	PULSE OUT (P/L)	
			L/MIN	GPM	BAR	PSI		PULSE VERSION	DISPLAY VERSION
FOO40710A	K24 METER (1 SOCKET)	Ad W	5 · 120	1,3-26,4	10	145	YES	-	-
FOO40721B	K24 PULSE-METER (1 SOCKET) (87,73 PULSE/L)	Ad W	5 · 120	1,3-26,4	10	145	NO	88	-

K24



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

TURBINOX

FEATURES

- LONG LASTING
- INDUSTRIAL APPLICATION
- STAINLESS STEEL BODY
- VERSATILE

The PIUSI TURBINOX is a turbine pulse meter suitable for transferring AdBlue®. Its stainless steel body guarantees a long-lasting resistance and makes this meter perfect for plant installations.

PERFORMANCE

UP TO

40 L/MIN

FLOW RATE

20 BAR

MAX

OPERATING PRESSURE

±1%

ACCURACY

0,4%

REPEATABILITY

**TURBINOX - TURBINOX 90°**

PACKAGING

CODE	WEIGHT		PACKAGING		
	KG	LBS	MM	INCH	PCS/BOX
FOO420000A	0,5	1,1	80X80X75	3,1X3,1X3	1
FOO420001A	0,5	1,1	80X80X75	3,1X3,1X3	1
FOO410000	1,2	2,6	225X125X150	8,9X4,9X5,9	1



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER



WINDSCREEN

CHART



IN THE BOX


- TURBINOX METER
- INSTRUCTION MANUAL

DETAILS



TURBINE

DIMENSIONS



Dimensions expressed in millimeters

MATERIALS

- BODY: STAINLESS STEEL
- TURBINE: TECHNOPOLYMER

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		PRESSURE		DISPLAY	PULSE OUT (P/L)	
			L/MIN	GPM	BAR	PSI		PULSE VERSION	DISPLAY VERSION
FOO42000A	TURBINOX INLINE PULSE METER		10 - 40	2,6-10,6	20	290	NO	88	-
FOO42001A	TURBINOX 90° TURBINE PULSE METER		10 - 40	2,6-10,6	20	290	NO	88	-
FOO410000	TURBINOX 90° TURBINE PULSE METER W/DISPLAY UREA		10 - 40	2,6-10,6	20	290	YES	88	1 - 100

TURBINOX



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

MK325 METER

FEATURES

- MID EVALUATION CERTIFICATE
- LOW INVESTMENT INSTALLATION
- LOW MAINTENANCE COSTS
- BI-DIRECTIONAL MEASUREMENT
- ATEX PENDING
- EX-D PROTECTION

The PIUSI MK325 is a new and innovative flow meter specifically engineered for AdBlue® MID measuring. It can be installed both in fixed and mobile dispensing systems.

PERFORMANCE

 $\pm 0,3\%$

ACCURACY

20 BAR

MAX

OPERATING PRESSURE

 UP TO
35 L/MIN


FLOW RATE

0,2%

REPEATABILITY



MK325



ELECTRICAL SCHEME

PACKAGING

CODE	WEIGHT		PACKAGING		
	KG	LBS	MM	INCH	PCS/BOX
FOO476X00	22	4,85	190X140X160	7,48X5,51X6,3	1



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER



WINDSCREEN


CHART



TYPE OF FLUID WATER

TEMPERATURE 20°C

DIMENSIONS



Dimensions expressed in millimeters

IN THE BOX

- MK325 METER
- INSTRUCTIONS WITH CALIBRATION FACTOR
- INSTRUCTION MANUAL

DETAILS



1,5M CABLE LENGTH



ATEX CERTIFIED



PEEK GEAR



BIDIRECTIONAL MEASURING

MATERIALS

- BODY: STAINLESS STEEL
- CABLE BOX: ALLUMINIUM
- GEAR: PEEK
- SEALS: NPR

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		PRESSURE		DISPLAY	PULSE OUT (P/L)	
			L/MIN	GPM	BAR	PSI		PULSE VERSION	DISPLAY VERSION
FO0476X00	MK325 METER	Ad W	5 - 35	1,3 - 8-9,3	20	290	NO	APPROX. 160	NO

OTHER VERSION AVAILABLE ON REQUEST

MK325 METER

ELECTRONIC METERS

97



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

REMOTE DISPLAY

FEATURES

- **LARGE SCREEN DISPLAY**
- **NON RESETTABLE TOTAL**
- **STANDARD BATTERY**

REMOTE DISPLAY for remote control (via max. 15 m. cable) of pulse meters. The large screen displays the quantity delivered and the non resettable total. Equipped with software applications for calibrating meters. Available as both basic display device and as pulse emitter. Indispensable for receivers designed to recognise only discreet quantities of impulses. The easy interfacing management systems of the pulse transmitter models extend the field of application of pulse meters combined with remote displays.

PERFORMANCE

every

PULSE METER

COMPATIBILITY

UP TO

100**PULSES/LITER**

FLOW RATE



REMOTE DISPLAY



PACKAGING

CODE	WEIGHT		PACKAGING		
	KG	LBS	MM	INCH	PCS/BOX
FOO49502A	1,2	2,6	200X120X140	8,9X4,9X5,9	1
FOO49503B	1,2	2,6	225X125X150	8,9X4,9X5,9	1



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL







WATER



WINDSCREEN

FUNCTIONING




IN THE BOX

- REMOTE DISPLAY
- BRACKET
- INSTRUCTION MANUAL

DETAILS




5 DIGITS PARTIAL TOTAL



ADJUSTABLE BRACKET

DIMENSIONS



Dimensions expressed in millimeters

TECHNICAL DATA





CODE	DESCRIPTION	FLUIDS TYPE	FLANGE	INLET OUTLET
FOO49502A	DISPLAY PULSE IN		FOR ALL PIUSI PULSE OUT REMOTE DISPLAY	PULSE IN
FOO49503B	DISPLAY PULSE OUT ADBLUE®		TURBINOX / K24 PULSER	PULSE OUT






REMOTE DISPLAY





METERS ACCESSORIES

ELECTRONIC METERS

K24	CODE	DESCRIPTION	
	FOO49503B	REMOTE DISPLAY PULS OUT 100 UREA	  
	FOO49504A	REMOTE DISPLAY NO PULS OUT - UREA	
	F15484000	HOSETAIL D.19 90° W/RING NUT FOR K24	
	F15776000	SWIVEL M-F 1IN GAS PLASTIC MANUAL NOZZLE	
	F16073000	STAINLESS STEEL SOCKET 1"(20 PCS)BSP/BSP	
			FOO49503B FOO49504A F15484000 F16073000

TURBINOX	CODE	DESCRIPTION	
	FOO49503B	REMOTE DISPLAY PULS OUT 100 UREA	   
	FOO49504A	REMOTE DISPLAY NO PULS OUT - UREA	
	F15484000	HOSETAIL D.19 90° W/RING NUT FOR K24	
	F15776000	SWIVEL M-F 1IN GAS PLASTIC MANUAL NOZZLE	
	F16073000	STAINLESS STEEL SOCKET 1"(20 PCS)BSP/BSP	
			FOO49503B FOO49504A F15484000 F15776000 F16073000

MK325	CODE	DESCRIPTION	
	F19914000	KIT WALL MK324	
			F19914000





METERED NOZZLES



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS

METERED
NOZZLES

SB325_X METER

FEATURES

- **HEAVY DUTY**
- **VERSATILE**
- **BUILT-IN TURBINE METER**
- **BREAK-AWAY SYSTEM**
- **MULTI-FUNCTIONAL DISPLAY**

The PIUSI SB325_X METER is the patented automatic metered nozzle by PIUSI for AdBlue®. It is composed by an innovative technopolymer casing, a break-away system, a stainless steel spout and the K24 meter with $\pm 1\%$ accuracy. Safety is guaranteed by the break-away system. In the event that a vehicle accidentally drives away with the nozzle still in the tank, the spout is designed to detach from the nozzle. This system also allows for a quick repair by merely fitting a new spout onto the nozzle.

PERFORMANCE

UP TO

45 L/MIN

FLOW RATE

3,5 BAR

MAX

OPERATING PRESSURE

 $\pm 1\%$

ACCURACY

**SB325_X METER**

PACKAGING

CODE	WEIGHT		PACKAGING		
	KG	LBS	MM	INCH	PCS/BOX
FOO61701A	1,0	2,2	447X178X63	17,6X7X2,5	1



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER



WINDSCREEN

CHART



IN THE BOX

- SB325_X METERED NOZZLE
- INSTRUCTION MANUAL

DETAILS




MULTI-FUNCTIONAL DISPLAY



BREAK-AWAY SYSTEM

DIMENSIONS



Dimensions expressed in millimeters

MATERIALS

- SPOUT: STAINLESS STEEL
- BODY: TECHNOPOLYMER

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		MAGNETIC ADAPTOR	METER	PRESSURE	INLET	SWIVEL	SPOUT
			L/MIN	GPM			BAR			EXT. Ø
FO061701A	AUTOMATIC NOZZLE SB325_X METER	Ad W	45	12	NO	YES	3,5	3/4"	YES	19 MM

SB325_X METER

AUTOMATIC METERED NOZZLES

105



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS

METERED
NOZZLES

K24 A60 AUTOMATIC NOZZLE

FEATURES

- READY TO USE
- STURDY DESIGN
- STAINLESS STEEL BODY
- ROTABLE DISPLAY

The SUZZARABLU A60 nozzle with integrated K24 meter is the basic version for the dispensing of AdBlue® fitting an automatic nozzle and a flow meter. Made with materials compliant to ISO22241, this equipment automatically shuts off flow when the tank is full while ensuring the maximum precision with the K24 meter.

PERFORMANCE

UP TO

40 L/MIN

FLOW RATE

3,5 BAR

MAX

OPERATING PRESSURE

±1%

ACCURACY

19MM

OD SPOUT



K24 A60 AUTOMATIC NOZZLE

PACKAGING

CODE	WEIGHT		PACKAGING			BOXES/EUROPALLET	
	KG	LBS	MM	INCH	PCS/BOX		
F00870000	2,74	6,04	460X200X80	18,11X7,87X3,15	1	-	-



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER




WINDSCREEN

CHART



DIMENSIONS



Dimensions expressed in millimeters

IN THE BOX

- K24 A60 AUTOMATIC NOZZLE
- INSTRUCTION MANUAL

DETAILS



STAINLESS STEEL



AUTOMATIC STOP



K24 METER

MATERIALS

- SPOUT: STAINLESS STEEL
- BODY: STAINLESS STEEL

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		PRESSURE	INLET	SWIVEL	SPOUT
			L/MIN	GPM	BAR	BSP	-	MM
FO0870000	K24 METER U\W WITH NOZZLE A60 SS§		40	10,6	3,5	3/4"	NO	19

K24 A60 AUTOMATIC NOZZLE

AUTOMATIC METERED NOZZLES

107



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS

METERED
NOZZLES

K24 SUZZARABLU MANUAL NOZZLE

FEATURES

- READY TO USE
- ERGONOMIC GRAB
- LOW WEIGHT

The K24 SUZZARABLU MANUAL NOZZLE is a manual nozzle suitable for the delivery of AdBlue® and Windscreen washing liquid. It comes with the plastic version of the K24 meter.

PERFORMANCE

UP TO

80 L/MIN

FLOW RATE

3,4 BAR

MAX

OPERATING PRESSURE

±1%

ACCURACY

LESS THAN

1 KG

NOZZLE WEIGHT



K24 SUZZARABLU MANUAL NOZZLE



PACKAGING

CODE	WEIGHT		PACKAGING		
	KG	LBS	MM	INCH	PCS/BOX
FO0870020	1	2,2	300X390X390X260	11,8X15,4X10,2	1



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL



WATER




WINDSCREEN

CHART

K24 SUZZARABLU MANUAL NOZZLE



DIMENSIONS



Dimensions expressed in millimeters

IN THE BOX

- K24 SUZZARABLU MANUAL NOZZLE
- INSTRUCTION MANUAL

DETAILS



STAINLESS STEEL SPOUT



K24 METER

MATERIALS

- SPOUT: STAINLESS STEEL
- BODY: TECHNOPOLYMER

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		PRESSURE	INLET	SWIVEL	SPOUT
			L/MIN	GPM				
FO0870020	K24 SUZZARABLU MANUAL NOZZLE		5 - 80	1,3 - 21	3,4	3/4"	NO	3/4"

K24 SUZZARABLU MANUAL NOZZLE


MANUAL METERED NOZZLE




109



METERED NOZZLES ACCESSORIES

AUTOMATIC METERED NOZZLES

SB325_X METER	CODE	DESCRIPTION
	F1917400A	KIT FOR SB325_X WITH MISFILLING AND MAGNETIC ADAPTOR
	F18400000	PIUSI MAGNETIC ADAPTOR
	F15165000	ELAFIX 40 MAGNETIC ADAPTOR



F1917400A F15165000 F18400000





NOZZLES



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

SB325_X

FEATURES

- **HEAVY DUTY**
- **VERSATILE**
- **BREAK-AWAY SYSTEM**
- **ERGONOMIC DESIGN**

The SB325_X is the patented automatic nozzle by PIUSI for AdBlue®, equipped with break-away system and stainless steel spout. Designed in compliance with International Standards ISO/ FDIS 22241-4:2009, it also features a reliable, ergonomic, and flexible shell that protects the nozzle against weathering and UV radiation.

Safety is guaranteed by the break-away system. In the event that a vehicle accidentally drives away with the nozzle still in the tank, the spout is designed to detach from the nozzle. This system also allows for a quick repair by merely fitting a new spout onto the nozzle.

PERFORMANCE

UP TO

45 L/MIN

FLOW RATE

3,5 BAR

MAX

OPERATING PRESSURE

**SB325_X**

PACKAGING

CODE	WEIGHT		PACKAGING		
	KG	LBS	MM	INCH	PCS/BOX
FO061700A	0,7	1,5	447X178X85	17,6X7X2,5	1



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER



WINDSCREEN

CHART



IN THE BOX

- SB325_X NOZZLE
- INSTRUCTION MANUAL

DETAILS




STAINLESS STEEL SPOUT



BREAK-AWAY SYSTEM

DIMENSIONS



Dimensions expressed in millimeters

MATERIALS

- SPOUT: STAINLESS STEEL
- BODY: TECHNOPOLYMER

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		MAGNETIC ADAPTOR	METER	PRESSURE	INLET	SWIVEL	SPOUT
			L/MIN	GPM			BAR			EXT. Ø
FO061700A	AUTOMATIC NOZZLE SB325_X	Ad W	45	12	NO	NO	3,5	3/4"	YES	19 MM

SB325_X



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

SUZZARABLU A60

FEATURES

- READY TO USE
- STURDY DESIGN
- STAINLESS STEEL BODY

The PIUSI SUZZARABLU A60 is an automatic nozzle suitable to dispense AdBlue® featuring a device that stops the dispensing when the tank is full. It comes with a hose-tail fitting.

PERFORMANCE

UP TO


40 L/MIN

FLOW RATE

3,4 BAR

MAX

OPERATING PRESSURE

**SUZZARABLU A60**

PACKAGING

CODE	WEIGHT		PACKAGING		
	KG	LBS	MM	INCH	PCS/BOX
FOO61903B	2,6	5,7	357X357X275	14,1X14,1X10,8	1



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL




WATER



WINDSCREEN

CHART



IN THE BOX

- SUZZARABLU A60 NOZZLE
- INSTRUCTION MANUAL

DETAILS




STAINLESS STEEL SPOUT



AUTOMATIC STOP

DIMENSIONS



Dimensions expressed in millimeters

MATERIALS

- SPOUT: STAINLESS STEEL
- BODY: STAINLESS STEEL

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		PRESSURE	INLET	SWIVEL	SPOUT
			L/MIN	GPM				EXT. Ø
FO061903B	SUZZARABLU A60		40	21,1	3,4	3/4"	YES	3/4"

SUZZARABLU A60

AUTOMATIC NOZZLES

117



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

SUZZARABLU MANUAL NOZZLE

FEATURES

- READY TO USE
- ERGONOMIC GRAB
- LOW WEIGHT

The PIUSI SUZZARABLU MANUAL NOZZLE is the basic version of Suzzarablu nozzles designed to dispense AdBlue®. Among the manual devices, it is distinguished by its high efficiency thanks to the low flow resistance, and a very inexpensive operation.

PERFORMANCE

UP TO

80 L/MIN

FLOW RATE

3,4 BAR

MAX

OPERATING PRESSURE

**SUZZARABLU MANUAL NOZZLE**

PACKAGING

CODE	WEIGHT		PACKAGING		
	KG	LBS	MM	INCH	PCS/BOX
F14761000	0,2	0,4	800X480X300	31,5X18,9X11,8	1



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL



WATER




WINDSCREEN

CHART

SUZZARABLU MANUAL NOZZLE



DIMENSIONS



Dimensions expressed in millimeters

IN THE BOX

- SUZZARABLU MANUAL NOZZLE
- INSTRUCTION MANUAL

DETAILS



MATERIALS

- SPOUT: STAINLESS STEEL
- BODY: TECHNOPOLYMER

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		PRESSURE	INLET	SWIVEL	SPOUT
			L/MIN	GPM				EXT. Ø
F14761000	MANUAL NOZZLE		80	10,6	3,4	3/4"	NO	3/4"

SUZZARABLU MANUAL NOZZLE






MANUAL NOZZLE



119





NOZZLES ACCESSORIES

AUTOMATIC NOZZLES


SB325_X	CODE	DESCRIPTION				
	F1917400A	KIT FOR SB325_X WITH MISF AND MAG AD				
	R1917200A	KIT SPOUT SB325_X WITH MISFILLING				
	R1917300A	KIT SPOUT SB325_X WITHOUT MISFILLING				
	F18400000	PIUSI MAGNETIC ADAPTOR				
	F15165000	ELAFIX 40 MAGNETIC ADAPTOR				
			F1917400A	R1917200A R1917300A	F15165000	F18400000

SUZZARBLUE A60	CODE	DESCRIPTION	
	F16475000	CONNECTOR K24 AUTOMATIC NOZZLE	
			F16475000

MANUAL NOZZLE

SUZZARBLUE MAN. NOZ.	CODE	DESCRIPTION	
	F15776000	SWIVEL M-F 1IN GAS PLASTIC MANUAL NOZZLE	
			F15776000





FILTRATION





CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

3D FILTER

FEATURES

- 3-STEP FILTRATION
- HI-RESISTANCE CASE
- REMOVABLE CARTRIDGE
- TRANSPARENT CONTAINER

The PIUSI 3D FILTER is specifically designed to prevent the contamination of AdBlue® during transferring operation. Thanks to the highly efficient (β 200) mechanical filtration, it allows an extended life of the catalyst.

PERFORMANCE

200 μ

FILTERING CAPACITY

4 BAR

MAX

OPERATING PRESSURE

**3D FILTER**

PACKAGING

CODE	WEIGHT			PACKAGING		
	A MM.	B MM.	C MM.	WEIGHT KG.	DIMENSION MM.	FILTER HEAD PCS/BOX
FOO611D00	136	107	140	0,6	200X120X140	166X144X85
FOO611D1A	104	70	104	0,2	166X144X85	-



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL



WATER




WINDSCREEN

FUNCTIONING



Typical condition of the filter after 3650 liters dispensed. We recommend changing the filter cartridge once a year.



High efficiency (β 200) mechanical filtration of particulate by means of an incremental filter specifically developed for AdBlue®.

IN THE BOX


- 3D FILTER
- INSTRUCTION MANUAL

DETAILS



3D FILTER CARTRIDGE

DIMENSIONS



Dimensions expressed in millimeters

MATERIALS

- BODY: TECHNOPOLYMER
- CARTRIDGE: POLYPROPYLENE

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		INLET/OUTLET	WATER ABSORBING	EFFICIENCY	MICRO	PRESSION
			L/MIN	GPM			β	μ M	BAR
FOO611DOO	3D FILTER FOR ADBLUE		40	10,5	1"	-	200	70	4
FOO611D1A	3D FILTER CARTRIDGE		-	-	-	-	-	-	-

3D FILTER

FILTER

125



TANK MONITORING

A large, solid red triangle is positioned in the bottom right corner of the page, pointing towards the top right.



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

OCIO

FEATURES

- **READY TO USE**
- **BUILT-IN DISPLAY**
- **STAINLESS STEEL PROBE**

OCIO is the PIUSI's tank level indicator specifically designed for AdBlue® thanks to its stainless steel probe. It gives a real time indication of the fluid quantity inside the tank. It gives a real time indication of the fluid quantity inside the tank.

PERFORMANCE

UP TO

4MT

HEIGHT

TANK

±1%

FULL SCALE

ACCURACY

UP TO

50 MT

LENGTH

PROBE TUBE



OCIO



10 METERS HOSE



STAINLESS STEEL PROBE

PACKAGING

CODE	WEIGHT		PACKAGING		
	KG	LBS	MM	INCH	PCS/BOX
FO0755140	2,2	4,8	300X410X100	11,8X16,1X3,9	1
FO0755220	2,2	4,8	300X410X100	11,8X16,1X3,9	1



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL



WATER



WINDSCREEN

FUNCTIONING


FUEL LEVEL
10MM
MEASURED
RESOLUTION



FUEL VOLUME
20 LITRES
CALCULATED
RESOLUTION



FUEL %
1%
CALCULATED
RESOLUTION




IN THE BOX

- OCIO UNIT
- PROBE
- 10 MT TUBE
- INSTRUCTION MANUAL

DETAILS



DIMENSIONS



Dimensions expressed in millimeters

MATERIALS

- PROBE: STAINLESS STEEL
- TUBE: TECHNOPOLYMER

TECHNICAL DATA


CODE	DESCRIPTION	FLUIDS TYPE	VOLTAGE		RS EXIT
			AC V/Hz	POWER WATT	
FO0755140	LEVEL IND.OCIO LV230V 50/60 - ADBLUE	A B D O W	230/50	20	AVAILABLE
FO0755220	LEVEL IND. OCIO 2.0 RS485 230V 50/60	A B D O W	230/50	20	AVAILABLE



OCIO



TANK MONITORING ACCESSORIES

TANK LEVEL INDICATOR

OCIO	CODE	DESCRIPTION
	F1391300A	KIT TUBO OCIO L-50MT
	F15611000	STAINLESS STEEL PROBE FOR ADBLUE - OCIO


F1391300A F15611000





HOSE REEL

A large, solid red triangle is positioned in the bottom right corner of the page, pointing towards the top right.



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

ADBLUE® HOSE REEL

FEATURES

- HEAVY DUTY SPRING
- BUILT-IN HAND PROTECTION
- LONG LASTING

The PIUSI ADBLUE® HOSE REEL for AdBlue®, entirely Made in Italy, features a built-in heavy duty spring. It can be installed on a wall or inside closed cabinets. It is available both with or without hose.

PERFORMANCE

10 BAR
MAX

OPERATING PRESSURE

15 M

HOSE LENGTH



ADBLUE® HOSE REEL



PACKAGING

CODE	WEIGHT		PACKAGING			N. BOXES / EUROPALLET	
	KG	LBS	MM	INCH	PCS/BOX	✕	🚚
WITHOUT HOSE							
FO075006A	14	30,9	550X260X540	21X10X20	1	12	20
WITH HOSE							
FO075007C	17	37,5	550X260X540	21X10X20	1	12	20
FO075011B	24	52,9	550X260X540	21X10X20	1	12	20



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL



WATER




WINDSCREEN


INSTALLATION

Different ways to install PIUSI's hose reels: they can be easily placed wherever you need them without any problem about functionality and safety. PIUSI's products are without a doubt designed to support your work in any condition.


ROOF INSTALLATION



WALL INSTALLATION



GROUND INSTALLATION



IN THE BOX

- ADBLUE® HOSE REEL
- ACCESSORIES INCLUDED
- FIX SUPPORT PLATE (ON REQUEST)
- ROTATING SUPPORT PLATE (ON REQUEST)
- INSTRUCTION MANUAL

DETAILS




HAND PROTECTION



ACCESSORIES INCLUDED

DIMENSIONS

MODEL	OPEN HOSE REEL BIG	OPEN HOSE REEL SMALL
A	495	475
B	460	460
C	152	102
D	200	150
E	246	196
F	150	150
G	200	150
H	12	12






Dimensions expressed in millimeters

MATERIALS

- BODY: CAST IRON
- HUB: POLYPROPYLENE
- TUBE: RUBBER

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	HOSE*	MAX OPERATING PRESSURE (BAR)	PRESSURE DROP	INLET	OUTLET	HOSE MAX LENGTH BOUND* (METERS)	HOSE LENGTH
			BPS		TYPE	WITH HOSETAIL BSP	BSP		METER
WITHOUT HOSE									
FO075006A	ADBLUE HOSE REEL -" BSP W/O HOSE SMALL		3/4"	10	0,1 @ 35 L/MIN	3/4"	3/4"	9,5	-
WITH HOSE									
FO075007C	ADBLUE HOSE REEL -" BSP W/HOSE 8MT		3/4"	10	0,4 @ 35 L/MIN	3/4"	3/4"	-	8
FO075011B	ADBLUE HOSE REEL -" BSP W/HOSE 15MT		3/4"	10	0,6 @ 35 L/MIN	3/4"	3/4"	-	15

ADBLUE® HOSE REEL





OPEN HOSE REEL

135



HOSE REELS ACCESSORIES

OPEN HOSE REEL

ADBLUE® HOSE REEL	CODE	DESCRIPTION
	F1731600A	SMALL HOSE REEL FIXED BASE
	F1731700A	SMALL HOSE REEL ROTATING SUPPORT
	F17275000	KIT PLATE HOSE REEL TANK IBC
	F1629800A	BIG HOSE REEL FIXED BASE
	F1627900A	BIG HOSE REEL ROTATING SUPPORT
	F1818700A	CLAMP D.27-29 HOSEREEL UREA/SMALL
  		
F1731600A F1629800A		F1731700A F1627900A
F17275000		





ACCESSORIES





CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

CONNECTIONS&CONNECTORS

FEATURES

- SEVERAL SHAPES
- PERFECTLY FIT EVERY EQUIPMENT
- COMPLIANT TO ISO22241 NORM

The PIUSI range of CONNECTIONS & CONNECTORS for AdBlue® is manufactured with materials compliant to the ISO22241 norm: AF2 or SEC that perfectly fits every application context, KIT BOTTOM CONNECTION, SUCTION CONNECTION and GRAVITY KIT for non-electric fluid transfer.


CONNECTIONS

TECHNICAL DATA

CODE	DESCRIPTION	FLUID	LENGTH	INLET / OUTLET		HOSE	PIECES/BOX
			METERS (M)	A	B	Ø (MM)	


GRAVITY KIT

F1551700A	SUZZARA BLUE GRAVITY KIT		3 M	F 2" BSP	NOZZLE	-	1
-----------	--------------------------	-----------------------------------------------------------------------------------	-----	----------	--------	---	---



SUZZARABLU GRAVITY KIT

KIT BOTTOM CONNECTION

F15515010	KIT BOTTOM CONNECTION W/FOOT VALVE 0.3MT		0,3 M	F 2" BSP	1" X D.25	-	1
F15515000	KIT BOTTOM CONNECTION W/FOOT VALVE 1.5MT		1,5 M	F 2" BSP	1" X D.25	-	1







F15515010



F15515000

SUCTION CONNECTION

F15606020	SUCTION DIP TUBE SUZZARABLU 2" BSP		0,5 M	D.20 MM	2" BSP	-	1
F15606000	SUCTION DIP TUBE SUZZARABLU 56X4		0,5 M	D.20 MM	56X4 BUTT	-	1
F15606010	SUCTION DIP TUBE SUZZARABLU 2" BUTT		0,5 M	D.20 MM	2" BUTT	-	1



SUCTION CONNECTION



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL



WATER



WINDSCREEN

CONNECTORS

TECHNICAL DATA

CODE	DESCRIPTION	FLUID	LENGTH	INLET / OUTLET		HOSE	PIECES/BOX
			METERS (M)	A	B	Ø (MM)	

AF2

F20189000	AF2 56X4 BUTTRESS / M 1"		-	56X4 BUTT	M 1"	-	1
F20190000	AF2 2" BUTTRESS / M 1"		-	2" BUTT	M 1"	-	1
F20257000	AF2 2" BSP / M 1"		-	2" BSP	M 1"	-	1
F20258000	AF2 2" 70X6 / M 1"		-	2" 70X6	M 1"	-	1



AF2

SEC

F15339000	SEC CONNECTOR / M 3/4"		-	SEC	M 3/4"	-	1
F15452000	SEC CONNECTOR + HOSE TAIL 90° M 3/4"		-	SEC	M 3/4"	-	1



SEC



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

COUPLING & FITTINGS

FEATURES

- **STURDY DESIGN**
- **PERFECTLY FIT EVERY EQUIPMENT**
- **COMPLIANT TO ISO22241 NORM**



Safe, sturdy and reliable: the PIUSI range of COUPLING & FITTINGS is expressly engineered for AdBlue® (compliant to ISO22241 norm). Several shapes and dimensions make this range suitable for every use.

COUPLING & FITTINGS

TECHNICAL DATA

CODE	DESCRIPTION	FLUID	LENGTH	INLET / OUTLET		HOSE	PIECES/BOX
			METERS (M)	A	B	Ø (MM)	

HOSETAILS

F15522000	HOSETAIL M 1" X D.20 PLASTIC	 	-	M 1" BSP	-	20	1
F16435000	HOSETAIL F 1" X D.20 WITH NUT	 	-	F 1" BSP	-	20	1











F15522000



F16435000

ELBOWS

F15484000	HOSETAIL 90° D.19 F 1" BSP FOR K24 METER	 	-	F 1" BSP	-	19	1
F15450000	HOSETAIL 90° D.19 F 3/4" BSP	 	-	F 3/4" BSP	-	19	1
F16433000	PIPE FITTING 90° 2/F 1" BSP RING	 	-	F 1" BSP	-	-	1
F15485000	HOSETAIL 90° D.19 1" BSP W/NUT W/NIPPLE	 	-	1" BSP	-	19	1



F15484000



F15450000





F16433000



F15485000

FITTINGS

F16434000	STRAIGHT CONNECTION WITH 2 NUTS F 1" BSP	 	-	F 1" BSP	F 1" BSP	-	1
------------------	------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---	----------	----------	---	---



F16434000



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL



WATER



WINDSCREEN

COUPLING&FITTINGS

TECHNICAL DATA

CODE	DESCRIPTION	FLUID	LENGTH	INLET / OUTLET		HOSE	PIECES/BOX
			METERS (M)	A	B	Ø (MM)	

SLEEVE

F16073000	SLEEVE F 1" BSP / F 1" BSP (20 PCS) SS		-	F 1" BSP	F 1" BSP	-	20
F16074000	SLEEVE F 1" NPT / F 1" NPT (20 PCS) SS		-	F 1" NPT	F 1" NPT	-	20
F16458000	SLEEVE F 1" NPT / F 1" BSP (20 PCS) SS		-	F 1" NPT	F 1" BSP	-	20




F16073000
F16074000
F16458000

COUPLINGS



F15176000	NIPPLE M 1" BSP / M 1" BSP PLASTIC		-	M 1" BSP	M 1" BSP	-	1
-----------	------------------------------------	--	---	----------	----------	---	---



F15176000

SWIVEL UNION



F15776000	SWIVEL UNION M 1" BSP / F 1" BSP		-	M 1" BSP	F 1" BSP	-	1
-----------	----------------------------------	--	---	----------	----------	---	---



F15776000

COUPLING&FITTINGS

ACCESSORIES

143



CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

HOSE&SWIVEL

FEATURES

- SEVERAL LENGTH
- WIDE ARRAY OF SHAPES
- COMPLIANT TO ISO22241 NORM

PIUSI has designed a complete range of HOSES&SWIVEL for AdBlue® that meets the most common usages requirements: rigid or flexible hoses to be used inside or outside the tanks, crimped, spiral, submersible and non submersible hoses; all compliant to ISO22241 norm.

HOSE&SWIVEL

TECHNICAL DATA

CODE	DESCRIPTION	FLUID	LENGTH	INLET / OUTLET		HOSE	PIECES/BOX
			METERS (M)	A	B	Ø (MM)	

CLAMP

F1380000	STAINLESS STEEL CLAMPS (10PCS)	-	-	-	-	-	10
----------	--------------------------------	---	---	---	---	---	----



CLAMP

DELIVERY HOSES

F14250000	DELIVERY EPDM HOSE 3/4" 4MT		4 M	-	-	3/4" - 19	1
F14125020	DELIVERY EPDM HOSE 3/4" 6MT		6 M	-	-	3/4" - 19	1
F14125030	DELIVERY EPDM HOSE 3/4" 8MT		8 M	-	-	3/4" - 19	1
F14125040	DELIVERY EPDM HOSE 3/4" 10MT		10 M	-	-	3/4" - 19	1
F1412505A	DELIVERY EPDM HOSE 3/4" 50MT		50 M	-	-	3/4" - 19	1



DELIVERY HOSES

DELIVERY CRIMPED HOSES

F1907200A	DELIVERY EPDM CRIMPED HOSE F 3/4" BSP 6MT		6 M	F 3/4" BSP	-	3/4" - 19	1
-----------	-------------------------------------------	--	-----	------------	---	-----------	---



DELIVERY CRIMPED HOSES

SUBMERSIBLE SUCTION SPIRAL HOSES

F1412400B	SUCTION SPIRAL SS EPDM HOSE 3/4" 15MT		15 M	3/4"	-	3/4" - 19	1
F15883000	KIT SUCTION SPIRAL EPDM HOSE 1.1MT W/SEC		1,1 M	SEC	-	3/4" - 19	1



F1412400B



F15883000



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL



WATER



WINDSCREEN

HOSE&SWIVEL

TECHNICAL DATA

CODE	DESCRIPTION	FLUID	LENGTH	INLET / OUTLET		HOSE	PIECES/BOX
			METERS (M)	A	B	Ø (MM)	

NON SUBMERSIBLE SUCTION SPIRAL HOSES

F14146000	KIT SUCTION HOSE EPDM 1,5MT W/FOOT VALVE		1,5 M	FOOT VALVE	-	3/4" - 19	1
F1424900A	SUCTION SPIRAL EPDM HOSE 3/4" 1.5MT		1,5 M	-	-	3/4" - 19	1
F19014000	SUCTION SPIRAL EPDM HOSE 3/4" 30MT		30 M	-	-	3/4" - 19	1
F19286000	SUCTION EPDM HOSE 3/4" 1.5MT CRIMP 1 SIDE		1,5 M	3/4"	-	3/4" - 19	1



F14146000



F1424900A



F19014000



F19286000

HOSE PROTECTION

F1649700A	RUBBER PROTECTOR FOR HOSE 3/4"		-	3/4"	-	-	1
-----------	--------------------------------	--	---	------	---	---	---



F1649700A

SWIVEL

F14132000	SWIVEL M 3/4" BSP X D.19 STAINLESS STEEL		-	M 3/4" BSP	-	19 MM	1
F15437000	SWIVEL M 3/4" BSP X D.25 STAINLESS STEEL		-	M 3/4" BSP	-	25 MM	1

F14132000
F15437000

HOSE&SWIVEL

ACCESSORIES

145



MERCHANDISE





CAR FILLING

FUEL MANAGEMENT
SYSTEMS

KITS



PUMPS



METERS



METERED NOZZLES

MERCHANDISE



PACKAGING

PRODUCTS

CODE	DESCRIPTION	WEIGHT		PACKAGING			
		KG	LBS	MM	INCH	PCS/PALLET	PCS/BOX
T-SHIRT BLACK							
PBG000031	PIUSI T-SHIRT BLACK BOX 10 PCS - L	1	-	35X26X18	-	-	10
PBG000032	PIUSI T-SHIRT BLACK BOX 10 PCS - XL	1	-	35X26X18	-	-	10
T-SHIRT WHITE							
PBG000026	PIUSI T-SHIRT WHITE BOX 10 PCS - L	1	-	35X26X18	-	-	10
PBG000027	PIUSI T-SHIRT WHITE BOX 10 PCS - XL	1	-	35X26X18	-	-	10
PBG000029	PIUSI T-SHIRT WHITE BOX 10 PCS - M	1	-	35X26X18	-	-	10
WATER BOTTLE							
PBG000037	PIUSI WATER BOTTLE - BOX 20 PCS	-	-	-	-	-	20
CAP							
PBG000040	PIUSI CAP - BOX 10 PCS	-	-	-	-	-	10



NOZZLES



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

INDEX

**PACKAGING**

CODE	DESCRIPTION	WEIGHT		PACKAGING			
		KG	LBS	MM	INCH	PCS/PALLET	PCS/BOX
CROWNER							
PBA000013	PIUSI METALLIC FLOOR STAND	76	-	120X100 (PALLET)	-	1	-
POSTER							
PBP000003	KIT POSTERS PIUSI - BOX 10 PCS	0,2	-	70X12	-	-	10
UMBRELLA							
PBG000030	PIUSI UMBRELLA - BOX 10 PCS	5,5	-	35X26X18	-	-	10
BAG							
PBG000035	PIUSI BAG 2018 - BOX 150 PCS	18,5	-	-	-	-	150
SPORTSPACK							
PBG000039	PIUSI SPORTSPACK - BOX 30 PCS	-	-	-	-	-	30
KEYRING							
PBG000041	PIUSI KEYRING -BOX 100 PCS	-	-	-	-	-	100

MERCHANDISE

MERCHANDISE

149

PIUSI FLUIDS' INFORMATION

ABOUT ADBLUE®

PIUSI SpA has been a leading manufacturer of fuel and lubricant transfer equipment since 1953, with a particular focus on the supply of pumps, flow meters, compressors and measuring instruments.

Diesel Exhaust Fluid (DEF): New Directives aimed at reducing the emission of pollutants into the atmosphere are complied with by **installing a catalyser** on the truck (SCR), which requires the use of a **special liquid blend of water and urea known as AdBlue®**, Arla or AUS 32 depending on reference market.

Every truck has to be equipped with an additional tank to store this special liquid. On the basis of meticulous analyses of the issues relating to urea transfer, **PIUSI has developed a reliable range of products made with materials that are compatible** with this fluid.

AdBlue® is a non-toxic urea solution used for chemically reducing nitrogen oxide (NOx) levels in diesel engine exhaust gases.

With effect from **1 January 2005**, all new vehicles sold in Europe must comply with the **Euro 4 standard**, which significantly limits polluting emissions.

AdBlue® enables latest-generation heavy vehicles to meet the envisaged limits, without compromising the performance or efficiency of their engines in any way.

With over 40,000 pumps and transfer equipment for AdBlue®/DEF installed throughout Europe, PIUSI is helping companies and government bodies to reduce NOx emissions as required by European legislation.

PIUSI offers a comprehensive range of transfer equipment and dispensers for AdBlue®, including pumps, flow meters, nozzles and all the necessary accessories for Urea transfer units.

The units can be easily applied to and removed from IBC tanks and drums.

The company also offers a series of **solutions for monitoring fluid levels in tanks and the quantities dispensed** by users.



TYPE OF FLUIDS

AIR

A

ANTIFREEZE

A

AdBlue® (UREA)

Ad

BIODIESEL

B

DIESEL

D

FOOD

F

GASOLINE

G

GREASE

^RG

KEROSENE

K

OIL

O

WATER

W

WINDSCREEN

W_S

The intellectual property of this catalogue is assigned to all countries. Translation, reproduction, electronic storage and full or partial adaption by any means (including microfilms and photocopies) of its contents, without prior written authorisation from PIUSI S.p.a., entails a violation of PIUSI S.P.A's copyrights and constitutes an act of unfair competition. The products shown in the images of this catalogue are protected according to the regulation in force regarding industrial property. The information contained in this catalogue is as accurate as possible and complies, as far as possible, with existing regulations at the time of its publication. We therefore reserve the right to make subsequent modifications in line with modifications to regulations and/ or in relation to any production requirements that are deemed necessary for safety reasons. The technical specifications indicated in this catalogue cancel out and replace those already present in the previous general catalogue and in the product catalogues. The updates and product data sheets are available in PDF format on our website:

www.piusi.com



CERTIFIED
ISO 9001 / ISO 14001

SINCE 1953, PIUSI HAS BEEN EMPLOYING ITALIAN ENGINEERING SKILLS AT THE SERVICE OF ITS CUSTOMERS, WITH PROFESSIONALISM AND INTEGRITY IN ORDER TO BUILD STABLE AND LASTING RELATIONSHIPS.

OUR MISSION IS TO PROVIDE SIMPLE, INTELLIGENT AND PROFESSIONAL SOLUTIONS FOR THE TRANSFER, DISPENSE AND MEASUREMENT OF LUBRICANTS, FUELS AND LIQUIDS, WITH THE HIGHEST CONSIDERATION FOR HUMAN AND ENVIRONMENTAL HEALTH.



PIUSI S.p.A.
Headquarters
46029 Suzzara (Mantova) Italy
tel. +39 0376 534561
fax. +39 0376 536393
e-mail: piusi@piusi.com
www.piusi.com



PIUSI USA, Inc.
3901 Anglers Avenue
Fort Lauderdale, FL 33312
tel.: 954 584 1552
fax.: 954 584 1554
Email: piusiusa@piusiusa.com
www.piusiusa.com